

LG 110UM5K Digital signage flat panel 2.79 m (110") LCD Wi-Fi 500 cd/m² 4K Ultra HD Black WebOS 16/7

Gamintojas: **LG ELECTRONICS** · Modelis: **110UM5K-B** · EAN: **8806084240859** · Prekės kodas: **489462**



15 447,90 €

Kaina su PVM

Be PVM: **12 766,86 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Brightness : 500 nit (Typ.)
- ✓ Resolution : ULTRA HD (3,840 x 2,160)
- ✓ Bezel : 17 mm (Even bezel)
- ✓ Built-in Speaker (10 W + 10 W)
- ✓ Interface : HDMI(3)/ DP/ DVI-D/ USB 2.0/ RS232C/ RJ45/ Audio/ IR



Aprašymas

UHD Large Screen Signage Display with LG webOS Platform

Super High Resolution

Delivering immersive viewing experience by 4 times higher definition picture quality than FHD.

Adequate Brightness Level

The UM5K series boasts an adequate brightness level of 500 cd/m² for indoor displays, effectively showcasing content and capturing the public's attention. This makes it an adequate display solution for marketing purposes in various settings, including meeting rooms, airports, retail outlets, and shopping malls.

High-Performance with webOS

LG webOS platform enhances user convenience with intuitive GUI and simple app development tools.

Built-in Speaker

Contents will be enriched with sound effects from built-in speakers, without the need for purchasing or installing external speakers.

Slim Design

Being slim, a closer installation to the wall is advised. Additionally, this increases the screen's immersive experience and provides a sophisticated design, improving the installed-space's décor.

Compatible with AV Control System

The UM5K series has supported Crestron Connected® for high compatibility with professional AV controls to achieve seamless integration and automated control, boosting business management efficiency.

SuperSign Solutions

SuperSign is an integrated and intuitive content management solution for creative and organized digital signage content in your space, connecting customers to a range of services with convenient user experiences. There are a variety of versions such as SuperSign Cloud, so discover and enjoy the version that best fits you.

Techninė specifikacija

Specifications	
Sandėlio grupė	[INN] INFO MONITORS > 55 [+26][-110]
Display	
Display diagonal	2.79 m (110")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	500 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	ADS
LED backlight	Yes
LED backlighting type	Direct-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	1000000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Panel life	50000 h
Colour depth	8 bit

Native refresh rate	120 Hz
Haze rate	25%
Ports & interfaces	
HDMI ports quantity	4
DVI port	Yes
DisplayPorts quantity	1
USB port	Yes
HDMI input ports quantity	3
HDMI output ports quantity	1
DVI-D ports quantity	1
USB ports quantity	1
USB version	2
USB connector type	USB Type-A
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
Remote (IR) input	1
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Panel mounting interface	1500 x 600 mm
Bezel width (bottom)	1.7 cm
Bezel width (side)	1.7 cm
Bezel width (top)	1.7 cm
Performance	
Purpose	Commercial
Picture-in-Picture	Yes
On Screen Display (OSD)	Yes

Operating hours (hours/days)	16/7
HDCP	Yes
Automatic brightness control	Yes
HDCP version	1.4/2.2/2.3
Power	
Power consumption (typical)	440 W
Power consumption (standby)	0.5 W
Power consumption (max)	570 W
AC input voltage	100-240 V
AC input frequency	50-60 Hz
Computer system	
Internal memory	16 GB
Operating system installed	WebOS
Operating system version	6
Weight & dimensions	
Display width	2474 mm
Display depth	99 mm
Display height	1408 mm
Display weight	80 kg
Packaging data	
Package width	2680 mm
Package depth	320 mm
Package height	1730 mm
Package weight	110 kg
Packaging content	
Remote control included	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Network	
Ethernet LAN	Yes
Wi-Fi	Yes
Other features	
Audio input	1

Audio output	1
Power consumption (PowerSave)	308 W
Plug and Play	Yes

Technical details

Real Time Clock (RTC)	Yes
-----------------------	-----

Matmenys ir svoris

Matmenys (I × P × A)	174,00cm × 35,00cm × 269,00cm
Svoris	110,00kg