

iiyama ProLite T2452MSC-B2AG kompiuterio monitorius 61 cm (24") 1920 x 1080 pikseliai „Full HD“ LED Lietimui jautrus ekranas Juoda

Gamintojas: **IIYAMA CONSIGNMENT** · Modelis: **T2452MSC-B2AG** · EAN: **4948570127245** · Prekės kodas: **496785**



394,90 €

Kaina su PVM

Be PVM: **326,36 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 61 cm (24") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekranas: Plokščias
- ✓ Maksimalus atnaujinimo dažnis: 120 Hz Reakcijos laikas: 5 ms
- ✓ Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1920 x 1080 pikseliai „Full HD“ Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP REACH, RoHS, WEEE





Aprašymas

Enjoy smooth and intuitive control with the ProLite T2452MSC-B2AG, a 24" Full HD touchscreen built for natural and precise touch. Its DeepContrast PCAP+ (Optical Bonded PCAP) 10-point touch technology ensures instant responsiveness, vivid contrast and reduced reflections thanks to optical bonding, in addition, the display is protected from moisture and potential condensation development. The anti-fingerprint and anti-glare coating keeps the screen clean and easy to read, while the IPS panel delivers rich colours and consistent image quality from any angle. Designed for comfort and efficiency, the adjustable stand supports ergonomic positioning, and the integrated cable management system keeps your workspace neat. With built-in audio and versatile connectivity (HDMI, DisplayPort, USB 3.2 hub), it offers a clean and flexible setup. Sleek edge-to-edge glass and a refined black design make it as stylish as it is functional – perfect for interactive signage, retail, POS, hospitality and creative spaces.

Techninė specifikacija


Display	
Display diagonal	61 cm (24")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1300:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Number of simultaneous touchpoints	10
Display brightness (typical)	420 cd/m²
Display brightness	360 cd/m²
Response time measurement type	GTG (Gray to Gray)
Anti-glare screen	Yes
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.275 x 0.275 mm

Horizontal scan range	30 - 138 kHz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Display diagonal (metric)	60.5 cm
Surface hardness	7H
Performance	
Flicker-free technology	Yes
Low Blue Light technology	Yes
Palm rejection	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W
Design	
Market positioning	Office
Product colour	Black
Front bezel colour	Black
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of downstream ports	2
USB Touch port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Headphone outputs	1
Headphone connectivity	3.5 mm
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm

Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	-5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	18 kWh
Power consumption (typical)	18 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Weight & dimensions	
Width (with stand)	567 mm
Depth (with stand)	253.5 mm
Height (with stand)	385 mm
Weight (with stand)	5.6 kg
Packaging data	
Package width	635 mm
Package depth	143 mm
Package height	405 mm
Package weight	7.1 kg
USB cable length	1.5 m
Packaging content	
Cables included	AC, USB, HDMI
Quick start guide	Yes
HDMI cable length	1.5 m
Power cable length	1.8 m
Sustainability	

Sustainability certificates	ErP
Other features	
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Positional accuracy	2 mm
Brightness	360 cd/m²
Packaging content	Screwdriver
Active display area (W x H)	527 x 296.5 mm
USB ports quantity	2
Weight	5.6 kg
Height	385 mm
Width	567 mm
Depth	253.5 mm
Compliance certificates	REACH, RoHS, WEEE
Mean time between failures (MTBF)	50000 h
User controls	Picture adjust (brightness, contrast, i-Style Color, adv. contrast, ECO, OverDrive, X-Res technology), color settings (gamma, RGB range, color temp.), image settings (video mode adjust, blue light reducer, sharp and soft), OSD (horizontal pos., vertical pos., OSD time, OSD background, language, display information), extra (reset, DDC/CI, signal select, volume, mute, led, opening logo, touch switch)
Touch method	stylus, finger, glove (latex)
Control panel	Menu, scroll up / ECO, scroll down / volume, select / input, power
Technical details	
Native refresh rate	120 Hz
Matmenys ir svoris	
Matmenys (I × P × A)	64,00cm × 40,00cm × 14,00cm
Svoris	7,04kg

Energijos efektyvumas ir ekologinis projektavimas



18 kWh/1000h



2019/10/13

Energijos efektyvumo klasė

E A-G

- > [Energijos etiketė](#)
- > [Gaminio informacijos lapas](#)
- > [EPREL duomenų bazė](#)

Dokumentai ir vaizdo įrašai

- > [Naudojimo instrukcija](#)
- > [Gaminio lankstinukas](#)
- > [Vaizdo įrašas 1](#) [objects.icecat.biz/objects/140733131_74873862.mp4](#)
- > [Vaizdo įrašas 2](#) [objects.icecat.biz/objects/140733131_74873864.mp4](#)
- > [Vaizdo įrašas 3](#) [objects.icecat.biz/objects/140733131_74873865.mp4](#)
- > [Vaizdo įrašas 4](#) [objects.icecat.biz/objects/140733131_74873866.mp4](#)

Gamintojo ir saugos informacija

GAMINTOJAS

iiyama International

Wijkmeesterstraat 8, 2131 HA Hoofddorp, NL

iiyama.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt