

iiyama ProLite T2438MSC-B2 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LED Touchscreen Black

Gamintojas: **IIYAMA CONSIGNMENT** · Modelis: **T2438MSC-B2** · EAN: **4948570127276** · Prekės kodas: **496789**



571,89 €

Kaina su PVM

Be PVM: **472,64 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 60.5 cm (23.8") Black
- ✓ Built-in speaker(s)
- ✓ HDMI DisplayPorts quantity: 1
- ✓ Screen shape: Flat
- ✓ Maximum refresh rate: 120 Hz Response time: 5 ms Response time measurement type: GTG (Gray to Gray)
- ✓ 1920 x 1080 pixels Full HD Panel type: IPS
- ✓ Energy efficiency class (SDR): E ErP CE, cTUVus, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE



Aprašymas

The ProLite T2438MSC-B2 is a responsive and reliable 24" Full HD touchscreen monitor designed for both demanding environments and everyday commercial use. The IPS panel delivers clear, vibrant images with wide viewing angles, ensuring excellent visibility at workstations, service counters or customer-facing installations. DeepContrast PCAP+ (Optical Bonding) 10-point touch technology provides smooth and accurate interaction for intuitive daily use. The edge-to-edge glass is scratch-resistant (7H) and features an anti-fingerprint coating, helping the screen stay clean and professional-looking even with frequent touch. Protection against humidity and dripping water (IPX1) adds extra confidence in busy workplaces. A robust metal housing ensures long-term durability, while the adjustable angle stand and integrated cable management create a tidy, ergonomic setup. With built-in speakers and flexible connectivity including HDMI, DisplayPort and a USB 3.2 hub, this monitor adapts easily to different installations. Supporting landscape, portrait and face-up orientations, it is a versatile solution for retail, POS, interactive signage and professional workspaces in demanding environments.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Large Format [+87][-114]
Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1300:1
Maximum refresh rate	120 Hz
Display number of colours	16.7 million colours
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (typical)	600 cd/m²
Display brightness	525 cd/m²
Response time measurement type	GTG (Gray to Gray)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.275 x 0.275 mm
Horizontal scan range	30 - 138 kHz
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Display diagonal (metric)	60.5 cm
DDC/CI	Yes
Surface hardness	7H
Colour depth	8 bit
Performance	
Flicker-free technology	Yes

Low Blue Light technology	Yes
Multimedia	
Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	4 W
Design	
Market positioning	Industrial
Product colour	Black
Housing material	Metal
Front bezel colour	Black
Glass thickness	3.6 mm
Ports & interfaces	
Built-in USB hub	Yes
HDMI	Yes
USB hub version	3.2 Gen 1 (3.1 Gen 1)
Number of downstream ports	2
USB Touch port	Yes
HDMI ports quantity	1
DisplayPorts quantity	1
Audio output	Yes
HDCP	Yes
Ergonomics	
VESA mounting	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	German, English, Spanish, French, Italian, Japanese, Dutch, Polish, Portuguese, Russian
Number of OSD languages	10
Plug and Play	Yes
Power	
Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	18 kWh

Power consumption (typical)	22 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G

Weight & dimensions

Width (with stand)	562 mm
Depth (with stand)	240 mm
Height (with stand)	366 mm
Weight (with stand)	8 kg
Bezel width (side)	1.73 cm
Bezel width (top)	2.03 cm
Bezel width (bottom)	2.03 cm

Packaging data

Package width	650 mm
Package depth	150 mm
Package height	430 mm
Package weight	10 kg
USB cable length	1.5 m

Packaging content

Cables included	AC, USB, HDMI
Quick start guide	Yes
HDMI cable length	1.5 m
Power cable length	1.8 m

Sustainability

Sustainability certificates	ErP
-----------------------------	-----

Other features

International Protection (IP) code	IP1X
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Positional accuracy	2 mm
Brightness	525 cd/m ²

Packaging content	Screwdriver
Active display area (W x H)	527 x 296.5 mm
USB ports quantity	2
Weight	8 kg
Height	366 mm
Width	562 mm
Depth	240 mm
Compliance certificates	CE, cTUVus, EAC, REACH, RoHS, TÜV mark, UKCA, WEEE
Mean time between failures (MTBF)	50000 h
User controls	Picture adjust (brightness, contrast, i-Style color, adv. contrast, ECO mode, OD, X-Res), color settings (gamma, RGB range, color. temp.), image settings (video mode adjust, blue light reducer, sharp & soft), OSD (H. pos., V. pos., time, background, rotate, language, display information), extra (reset, DDC/CI, signal select, volume, mute, led, opening logo, touch switch)
Touch method	finger, glove (latex), capacitive stylus
Control panel	Menu, Scroll up/ Eco, Scroll down/ Volume, Enter/ Input select, Power
Technical details	
Native refresh rate	120 Hz
Matmenys ir svoris	
Matmenys (I × P × A)	65,00cm × 43,00cm × 16,00cm
Svoris	10,04kg