

CyberPower CP1600EIPFCLCD uninterruptible power supply (UPS) Line-Interactive 1.6 kVA 1000 W 6 AC outlet(s)

Gamintojas: CYBERPOWER · Modelis: CP1600EIPFCLCD · EAN: 4711027797946 · Prekės kodas: 497283



454,90 €

Kaina su PVM

Be PVM: 375,95 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-Interactive
- ✓ 1.6 kVA 1000 W
- ✓ Waveform: Pure sine
- ✓ 6 AC outlet(s)
- ✓ Sealed Lead Acid (VRLA)
- ✓ Tower Black



Techninė specifikacija

Specifications

Sandėlio grupė

Stromversorgung > USV [+474][-335]

Features

UPS topology	Line-Interactive
Output power capacity	1.6 kVA
Output power	1000 W
Waveform	Pure sine

Input operation voltage (min)	169 V
Input operation voltage (max)	271 V
Input frequency	50/60 Hz
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Maximum current	10 A
Surge energy rating	405 J
Response time	8 ms
Heat dissipation	24 BTU/h
Power Factor Correction (PFC) type	Active
Surge protection	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Power source type	AC
Detachable power cord	Yes
Socket circuit breaker	Yes

Ports & interfaces

AC outlet types	C13 coupler, Type F
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	2
USB port type	USB Type A/USB Type-C
Serial interface	Yes
Ethernet LAN (RJ-45) ports	2

Battery

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	2.6 min
Typical backup time at half load	9.7 min
Battery recharge time	8 h

Design

Form factor	Tower
Product colour	Black
Cable length	1.83 m
Control type	Buttons

Display type	LCD
LED indicators	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Batteries included	Yes
Quick installation guide	Yes
Weight & dimensions	
Width	100 mm
Depth	355 mm
Height	280 mm
Weight	11 kg
Packaging data	
Package width	195 mm
Package depth	466 mm
Package height	370 mm
Package weight	13 kg
Other features	
Nominal output voltage	230 V
Nominal input voltage	220-240 V
Overload protection	Yes
Sustainability	
Sustainability compliance	Yes