

CyberPower CP550EPFCLCD uninterruptible power supply (UPS) Line-Interactive 0.55 kVA 350 W 6 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **CP550EPFCLCD** · EAN: **4712856276893** · Prekės kodas: **497315**



264,91 €

Kaina su PVM

Be PVM: **218,93 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Line-interactive UPS Topology
- ✓ Active PFC Compatible
- ✓ Automatic Voltage Regulation (AVR)
- ✓ LED Status Indicator
- ✓ Surge and Spike Protection
- ✓ Tower Form Factor
- ✓ Energy Saving Technology
- ✓ Pure Sine Wave Output
- ✓ LCD Status Display
- ✓ PowerPanel Management Software



Aprašymas

CyberPower CP550EPFCLCD with Pure Sine Wave output safeguards mid- to high-end computer systems, servers and networking hardware that use conventional and Active Power Factor Correction (PFC) power supplies. Designed with GreenPower UPS™ Technology to improve UPS operating efficiency and to minimize its energy consumption, users can enjoy significant energy cost savings over conventional UPS systems.

The UPS provides Automatic Voltage Regulation (AVR) to maintain safe voltage levels for connected equipment. Featured data line protection guards phones, networks, and communication equipment against surges/spikes and other power irregularities. With multifunction LCD display, users can access information of power/battery conditions and configure advanced settings, including alert of potential power problems and self-test with a single push of a button.

Techninė specifikacija

Specifications	
Sandėlio grupė	Stromversorgung > USV [+474][-335]
Features	
UPS topology	Line-Interactive
Output power capacity	0.55 kVA
Output power	350 W
Waveform	Sine
Input operation voltage (min)	170 V
Input operation voltage (max)	270 V
Input frequency	50/60 Hz
Output operation voltage (min)	203 V
Output operation voltage (max)	230 V
Output frequency	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	405 J
Response time	4 ms
Heat dissipation	31 BTU/h
Efficiency	98.5%
Noise level	35 dB
Surge protection	Yes
Power protection features	Over voltage, Overload, Under voltage
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm
Auto-restart	Yes
Ports & interfaces	
Power plug	C14 coupler
AC outlets quantity	6 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Ethernet LAN (RJ-45) ports	2
Battery	
Battery technology	Sealed Lead Acid (VRLA)

Battery capacity	7 Ah
Battery voltage	12 V
Battery recharge time	8 h
Automatic battery test	Yes
Design	
Form factor	Mini Tower
Product colour	Black
Control type	Buttons
Display type	LCD
LED indicators	Status
Certificates	
Compliance certificates	CE, EAC, RCM, RoHS
Weight & dimensions	
Width	100 mm
Depth	275 mm
Height	230 mm
Weight	6.8 kg
Packaging data	
Package width	195 mm
Package depth	365 mm
Package height	335 mm
Package weight	7.6 kg
Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Other features	
Battery type	RBP0078
Sustainability	
Sustainability compliance	Yes