

ATEN 2-Port USB DVI KVM Switch with Audio

Gamintojas: **ATEN** · Modelis: **CS682-AT** · EAN: **4710423775909** · Prekės kodas: **497509**



70,91 €

Kaina su PVM

Be PVM: **58,60 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Superior video quality - up to 1920 x 1200 @ 60 Hz
- ✓ Computer selection via a remote port selector, hotkeys, and USB mouse
- ✓ Independent switching of the KVM and Audio focus - one computer has the KVM focus and the other the Audio focus
- ✓ Built-in all-in-one cables (2 x 1.2 m) and bus-powered design

Aprašymas

The CS682 takes a giant step forward from prior models in the Petite series, by offering DVI functionality, USB 2.0 peripheral sharing, and a rich bass experience for 2.1 surround systems. Another new feature of the CS682 is the implementation of a remote port selector. This means that you can now control port switching from the desktop while the switch itself can be placed in a convenient, out of the way, location.

1x CS682 2-Port USB 2.0 DVI KVM Switch

1x Remote Port Selector

1x User Instructions

Techninė specifikacija

Specifications

Sandėlio grupė

Telefon & Tablet > Schutzfolien [+507][165]

Ports & interfaces

Number of computers controlled	2
Keyboard port type	USB
Mouse port type	USB
Video port type	DVI-D

Console ports	3.5mm headphone, 3.5mm mic, DVI-D, USB A
DVI-D ports quantity	2
Console USB ports quantity	2
USB 2.0 Type-A hub ports quantity	4
USB connector type	USB Type-A, USB Type-B
Audio connections	Yes
Headphone outputs	3
Number of microphone inputs	3

Performance

HD type	WUXGA
Maximum resolution	1920 x 1200 pixels
Video bandwidth	60 Hz
Scan interval	3,5,10,20 s

Design

Rack mounting	No
Product colour	Black
LED indicators	Yes

Display

Built-in display	No
------------------	----

Power

Power source	DC
Input voltage	5 V
Power consumption (typical)	1.9 W

Operational conditions

Operating temperature (T-T)	0 - 50 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 80%
Storage relative humidity (H-H)	0 - 80%

Weight & dimensions

Width	111.5 mm
Depth	78 mm
Height	24 mm
Weight	460 g

Packaging data

Package width	70 mm
Package depth	163 mm
Package height	235 mm
Package weight	590 g
Packaging content	
Quick installation guide	Yes
Manual	Yes
Logistics data	
Master (outer) case net weight	4.6 kg
Harmonized System (HS) code	85176200
Master (outer) case width	395 mm
Master (outer) case length	405 mm
Master (outer) case height	182 mm
Master (outer) case gross weight	6.61 kg
Products per master (outer) case	10 pc(s)