

CLUB3D USB Gen1 Type-C, 6-in-1 Hub with HDMI 8K30Hz, 2xUSB Type-A, RJ45 and 2xUSB Type-C, Data and PD charging 100 watt

Gamintojas: CLUB 3D · Modelis: CSV-1596 · EAN: 8719214472344 · Prekės kodas: 497579



98,91 €

Kaina su PVM

Be PVM: 81,74 €

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Host interface: USB 3.2 Gen 1 (3.1 Gen 1) Type-C
- ✓ USB Power Delivery (USB PD)
- ✓ 100,1000 Mbit/s
- ✓ Plug and Play



Aprašymas

The Club 3D CSV-1596 is a USB Gen1 Type-C, 6-in-1 Hub with HDMI™ 8K30Hz-4K120Hz, 2xUSB Type-A, RJ45 and 2xUSB Type-C, Data and PD charging 100 watt, providing an ideal solution for extending the port of Type-C/Thunderbolt host (PC/Laptop/Mobile phone, etc.), especially for those host with a single Type-C port. This hub adopts the latest DP1.4 Alt mode supported IC, enabling to output HDMI™ video with max. 8K30Hz-4K120Hz and at the meanwhile transfer USB 3.1 data with max 5Gbps. The USB Type-A and Type-C data ports allow you to connect 4 USB devices simultaneously. 1 Gigabit Ethernet for super fast Ethernet. Besides, the Type-C female supports PD 3.0 PD Charging 100W (15W is dedicated to the functioning of this product, the rest power(max 85W) will be passed to charge for the host. This 6-in-1 Hub will work on all DP Alt mode supported Type-C hosts.

Techninė specifikacija

Ports & interfaces

Host interface	USB 3.2 Gen 1 (3.1 Gen 1) Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
HDMI ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	100 W
DC-in jack	No
HDCP	Yes
HDCP version	1.4/2.3
USB Type-C DisplayPort Alternate Mode	Yes
Network	
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	100,1000 Mbit/s
Performance	
Product colour	Black
Card reader integrated	No
HD type	8K Ultra HD
Number of displays supported	1
Maximum refresh rate	120 Hz
High Dynamic Range (HDR) supported	Yes
Hub interfaces	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C
Plug and Play	Yes
Certification	ROHS, FCC, CE EMI
Power	
Output voltage	5 V
Output current	1.5 A
Power consumption (max)	7.5 W
Wireless charging	No
Software	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Weight & dimensions	
Width	126 mm

Depth	32 mm
Height	35 mm
Weight	89 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	70 mm
Package depth	35 mm
Package height	320 mm
Package weight	136 g
Packaging composition	
Plastic packaging weight	5 g
Paper/cardboard packaging weight	42 g
Total plastic packaging weight	0 g
Total paper/cardboard packaging weight	0 g
Logistics data	
Harmonized System (HS) code	84733020
Other features	
Cable length	0.3 m
Cable type	Round cable