

DELL Pro 55 Plus P5525QC Digital signage flat panel 138.8 cm (54.6") LCD 400 cd/m² 4K Ultra HD Black

Gamintojas: **DELL** · Modelis: **DELL-P5525QC** · EAN: **5397184821770** · Prekės kodas: **498121**



1 286,90 €

Kaina su PVM

Be PVM: **1 063,55 €**

Sandėlyje




Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Digital signage flat panel Black
- ✓ Ethernet LAN
- ✓ 138.8 cm (54.6") 3840 x 2160 pixels LCD 400 cd/m²
- ✓ Built-in speaker(s) 20 W
- ✓ Edge-LED 8 ms



Aprašymas

Made for team collaboration, this monitor provides up to 90W power delivery via USB-C and flexibility to include an OptiPlex Micro based on your needs.

Techninė specifikacija

Specifications

Sandėlio grupė

Peripherie & Desktop > Monitore [+1613][-584]

Display

Display diagonal	138.8 cm (54.6")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	400 cd/m²
HD type	4K Ultra HD
Touchscreen	No
Panel type	IPS
LED backlight	Yes
LED backlighting type	Edge-LED
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.07 billion colours
Pixel pitch	0.315 x 0.315 mm
Active display area (W x H)	1209.6 x 680.4 mm
Display diagonal (metric)	138.787 cm
Horizontal scan range	30 - 140 kHz
Vertical scan range	24 - 75 Hz
Supported graphics resolutions	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA), 1152 x 864 (XGA+), 1280 x 1024 (SXGA), 1280 x 800, 1600 x 1200 (UXGA), 1920 x 1080 (HD 1080), 2048 x 1152, 2560 x 1440, 3840 x 2160
Supported video modes	480p, 576p, 720p, 1080i, 1080p, 2160p
Colour depth	8 bit
Haze rate	25%
Surface hardness	3H
Colour gamut	72%
Ports & interfaces	
HDMI ports quantity	2
DVI port	No
DisplayPorts quantity	2
USB port	Yes
HDMI version	2
DisplayPort version	1.4
USB version	3.2 Gen 1 (3.1 Gen 1)

USB connector type	USB Type-A, USB Type-B, USB Type-C
USB 2.0 Type-B ports quantity	1
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	90 W
USB Type-C DisplayPort Alternate Mode	Yes
Ethernet LAN (RJ-45) ports	1
RS-232C	Yes
DC-in jack	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Panel mounting interface	300 x 400 mm
Bezel width (bottom)	2.85 cm
Bezel width (side)	1.89 cm
Bezel width (top)	1.89 cm
Anti-glare screen	Yes
Performance	
Purpose	Commercial
Power	
Power consumption (typical)	77.1 W
Power consumption (standby)	0.5 W
Power consumption (off)	0.3 W
Power consumption (max)	300 W
Energy efficiency class (SDR)	E
Energy consumption (SDR) per 1000 hours	77 kWh
AC input voltage	100-240 V

AC input frequency	50/60 Hz
Weight & dimensions	
Width	1247.4 mm
Depth	79.8 mm
Height	727.8 mm
Weight	22.4 kg
Packaging data	
Package weight	33.8 kg
Packaging content	
Remote control included	Yes
Cables included	AC, DisplayPort, HDMI, USB, USB Type-C
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 90%
Carbon footprint	
Total carbon footprint (kg of CO2e)	927
Carbon emissions, manufacturing (kg of CO2e)	377.29
Carbon emissions, logistics (kg of CO2e)	63.04
Carbon emissions, energy usage (kg of CO2e)	373.58
Carbon emissions, end-of-life (kg of CO2e)	112.17
PAIA version	GaBi version 1, 2024
Network	
Ethernet LAN	Yes
Technical details	
Sustainability certificates	ENERGY STAR, TCO
Doesn't contain	Arsenic, Mercury, PVC/BFR
Compliance certificates	RoHS
Other features	
Quick start guide	Yes
Remote control battery	AAA x 2
Matmenys ir svoris	
Matmenys (I × P × A)	142,00cm × 89,00cm × 22,00cm