

ICY BOX IB-DK8801-TB4 Wired Thunderbolt 4 Anthracite, Black

Gamintojas: **ICY BOX** · Modelis: **IB-DK8801-TB4** · EAN: **4250078172710** · Prekės kodas: **500794**



339,90 €

Kaina su PVM

Be PVM: **280,91 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ **SMARTER WORKSPACE:** The next generation of Thunderbolt 4 finally brings true PC connectivity to notebooks and other devices: fast transfer speeds, multi-functional ports and a desk without cable clutter
- ✓ **THUNDERBOLT 4 – THE FUTURE OF CONNECTIVITY:** Compatible with e.g. DisplayPort, PCIe and USB 4 as well as backwards compatible with previous Thunderbolt versions: it's the cable connection that trumps all others
- ✓ **THUNDERBOLT 4 AND GAMING:** Those using external PCIe devices in conjunction with the IB-DK8801-TB4 and a compatible TB4 system can now run games directly from an external NVMe SSD
- ✓ **IMMERSE IN DIVERSITY:** High resolutions for Thunderbolt 4 enabled devices. Increase visual productivity with Ultra HD image sharpness, contrast and colour depth via the available HDMI and Thunderbolt 4 connections
- ✓ **THUNDERBOLT 4 AND PD:** IB-DK8801-TB4 charges smartphones, notebooks and more, everything that requires less than 100 watts. The benefit: no need for a separate power supply



Aprašymas

What is Thunderbolt™ 4?

It is the superset standard that includes USB4®, DisplayPort™ and PCI Express (PCIe). With Thunderbolt™ 4, a data transfer rate of up to 40 Gbit/s (at 2 m cable length) as well as 32 GB/s PCIe data transfer must be guaranteed, at least one 100 W charging port must be available and wake-up from sleep mode must be possible.

What is the difference between Thunderbolt™ 3 and 4?

Theoretically, a Thunderbolt™ 3 device should be able to do the same as a Thunderbolt™ 4 device. However, compared to version 3, Thunderbolt™ 4 now has to meet much stricter standards to be certified. This includes, among other things, support for two 4K displays or one 8K display.

IB-DK8801-TB4 prevents cyber attacks

This is realised through Virtualisation Technology for Directed I/O (VT-d). It prevents physical DMA attacks by protecting PCIe peripherals from unauthorised access to memory using DMA remapping. Access is thus only allowed to an isolated and allocated memory of a specific device.

Techninė specifikacija

Specifications	
Sandėlio grupė	Notebook > Dockingstations/Hubs [+971][[-442]
Ports & interfaces	
Connectivity technology	Wired
Host interface	Thunderbolt 4
USB 2.0 ports quantity	0
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	0
HDMI ports quantity	1
Microphone in	No
Headphone outputs	1
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	4
USB Power Delivery (USB PD)	Yes
USB Power Delivery revision	3
USB Power Delivery up to	96 W
Thunderbolt ports quantity	3
Thunderbolt 4 ports quantity	2
Combo headphone/mic port	Yes
DC-in jack	Yes
USB Type-C DisplayPort Alternate Mode	Yes
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Ethernet LAN data rates	10,100,1000,2500 Mbit/s
Performance	
Product colour	Anthracite, Black
Card reader integrated	Yes
Compatible memory cards	SD

Data transfer rate	40 Gbit/s
HD type	8K Ultra HD
Number of displays supported	2
Maximum refresh rate	60 Hz
Cable lock slot	Yes
Cable lock slot type	Kensington
On/off switch	Yes
LED indicators	Yes
Plug and Play	Yes
UASP support	Yes
Housing material	Aluminium
Country of origin	China
Power	
Power source type	AC
AC input voltage	100-240 V
AC input frequency	50 - 60 Hz
Power supply	135 W
Output voltage	5 - 20 V
Output current	6.75 A
Software	
Windows operating systems supported	Yes
Mac operating systems supported	Yes
Weight & dimensions	
Width	200 mm
Depth	75 mm
Height	31 mm
Weight	435 g
Packaging data	
Quantity per pack	1 pc(s)
Package width	290 mm
Package depth	92 mm
Package height	158 mm
Package weight	1.4 kg
Packaging content	

Cables included	DC, Thunderbolt
Manual	Yes
Logistics data	
Products per master (outer) case	9 pc(s)
Master (outer) case width	305 mm
Master (outer) case length	315 mm
Master (outer) case height	500 mm
Master (outer) case gross weight	12.6 kg
Harmonized System (HS) code	84718000