



**Monitorius DELL
P2425HE Pro
Plus 23.8" FHD
IPS 100Hz
Verslo Hub
ekranas | 90W
USB-C PD, TÜV 4
žvaigždučių akių
komfortas**

Modelis: P2425HE

Gamintojas: DELL

EAN: 5397184821725

Prekės kodas: 504503

322.99€

Profesionalus našumas ir išskirtinis komfortas

DELL P2425HE Pro Plus monitorius sukurtas maksimaliam verslo našumui ir išskirtinei vizualinei gerovei. Šis 23.8 colio Full HD (1920x1080) monitorius turi pažangų IPS skydelį, užtikrinantį ryškius

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

vaizdus ir plačius 178° žiūrėjimo kampus. Be to, 100Hz atnaujinimo dažnis užtikrina sklandesnį vaizdą kasdienių užduočių metu, palyginti su standartiniais 60Hz modeliais.

Kaip galingas šakotuvo monitorius, P2425HE supaprastina jūsų darbo vietą, siūlydamas išsamias jungtis per vieną USB Type-C kabelį, kuris vienu metu perduoda vaizdo signalą, duomenis ir tiekia iki 90W energijos (PD) prijungtam nešiojamam kompiuteriui įkrauti.

Aukščiausios klasės akių komfortas ir aiškumas

Pasirūpinkite savo sveikata su pramonėje pirmaujančiu TÜV Rheinland 4 žvaigždučių akių komforto sertifikatu. Naudojant integruotas mažos mėlynos šviesos ir mirgėjimo technologijas (Dell ComfortView), P2425HE žymiai sumažina akių nuovargį, užtikrindamas maksimalų komfortą net ilgai dirbant.

- **IPS Skydelis:** Mėgaukitės nuosekliomis, tiksliais spalvomis (99% sRGB) ir plačiais 178°/178° žiūrėjimo kampais.
- **Sklandus judesys:** 100Hz atnaujinimo dažnis užtikrina pastebimai sklandesnį naršymą ir perėjimus.
- **Aukštas kontrastas:** 1500:1 kontrasto santykis užtikrina sodrias juodas ir ryškias baltas spalvas.

Integruotas USB-C šakotuvai ir jungiamumas

Paverskite savo monitorių centriniu prijungimo mazgu, pasižyminčiu puikiu prievadų lankstumu, taip sumažindami kabelių netvarką ant stalo.

- **90W Galios Tiekimas:** Įkraukite nešiojamąjį kompiuterį per „upstream“ USB Type-C prievadą, tuo pačiu metu rodydami turinį.
- **Integruotas šakotuvai:** Yra USB 3.2 Gen 1 „downstream“ prievadai (Type-A ir Type-C), skirti greitam išorinių įrenginių prijungimui.
- **Vaizdo įvestys:** Apima 2x DisplayPort 1.4 ir 1x HDMI 1.4 prievadus, plius USB Type-C su „DisplayPort Alternate Mode“ palaikymu.
- **Tinklo Prievadas:** Integruotas RJ-45 prievadas patikimam laidiniam tinklo ryšiui.

Visiškas ergonominis reguliavimas

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

Pritaikykite monitoriaus padėtį tobulam komfortui ir bendram darbui, laikydamiesi VESA montavimo standartų.

- **Reguliuojamas Aukštis:** Iki 150 mm aukščio reguliavimo diapazonas.
- **Pivot Funkcija:** Pasukite ekraną 90 laipsnių, kad galėtumėte dirbti portreto režimu.
- **Pasukimas ir Palenkimas:** Lengvai reguliuokite pasukimą (nuo -45° iki 45°) ir palenkimą (nuo -5° iki 21°).
- **VESA Palaikymas:** 100 x 100 mm tvirtinimo sąsaja.

DELL yra pasaulinis technologijų lyderis, žinomas dėl patikimų, novatoriškų ir tvarių kompiuterinių sprendimų, skirtų profesionalams ir įmonėms visame pasaulyje. Šis monitorius atitinka griežtus tvarumo sertifikatus, įskaitant ENERGY STAR, TCO ir RoHS.

Užsisakykite šiandien iš ++SHOP++, nes mes siūlome geriausias kainas ir greitą aukštos kokybės DELL monitorių pristatymą.

Connect to productivity. Certified by TÜV for 4-star eye comfort, this FHD hub monitor offers enhanced visual comfort and offers up to 90W of power delivery.

Connect to productivity. Certified by TÜV for 4-star eye comfort, this FHD hub monitor offers enhanced visual comfort and offers up to 90W of power delivery.

- 60.5cm (23.8") Full HD 1920 x 1080 LED IPS
- 8ms, 16:9, 250cd/m², 1500:1
- USB, HDMI, DisplayPort

Actual configuration might differ from illustration

Product Carbon Footprint (PCF):

1. Dell generally uses the PAIA (Product Attribute to Impact Algorithm)(<http://msl.mit.edu/projects/paia/main.html>) tool for product carbon footprint calculations.
2. Docking station related PCFs are extracted from corresponding LCAs and as such do not follow the PAIA methodology used for calculating other PCFs in this report.
3. PAIA method is developed by the Massachusetts Institute of Technology's Materials Systems

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Laboratory and partners.

4. All estimates of carbon footprint are uncertain. Dell Technologies reports the 5th and 95th percentile of the carbon footprint estimate to reflect this uncertainty wherever possible.

(<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>)

5. Please note the emission estimate in this report is calculated using the mean value along with the standard deviation for that product model.

6. Use of default inputs (i.e. not primary data) and assumptions on location of use and other fields can introduce a standard deviation which must be taken into account while completing the calculations.

7. Please note, PAIA uses the ecoinvent Database (<https://ecoinvent.org/the-ecoinvent-database/>) whenever primary data is not made available for calculations.

8. For client and commercial end user computing products, minimum configurations were assumed for calculations. For Server and Storage products, typical configurations or ENERGY STAR (<https://www.energystar.gov/products>) configurations were used for calculations.

9. Use Phase emissions were calculated based on the location of use as "Europe" i.e. the Use Phase emissions are not specific to a single country / location.

10. The report does provide an option for a total emissions number for manufacturing, transport and end of life while leaving the use phase emissions out, in case the customer uses their own calculation methodology for use phase emissions.

11. The lifetime usage assumption at the product family level is as follows: Desktop, Notebook - 4 years, Display - 5 years and Servers - 4 years.

12. For detailed assumptions please refer to the product datasheets in the Dell Technologies reports (<https://www.dell.com/en-us/dt/corporate/social-impact/advancing-sustainability/climate-action/product-carbon-footprints.htm#tab0=0>).

13. The results from the PAIA tool are liable to change over time as the methodology is improved and datasets are updated. The PAIA version used to calculate emissions has been indicated with each record in the report.

14. Metrics used: The units for global warming potential are in kgCO₂-equivalent or MT (metric ton) CO₂-equivalent (CO₂e).

15. Beginning in June 2024, the data dashboard now incorporates PCF values computed using the Dell PCF calculator. It's important to note that the default location utilized for these calculations shown on the data dashboard is Europe. To access PCF values calculated for the USA and China

locales, please refer to the Product PCF PDF document on Dell.com.

Summary: DELL P Series P2425HE. Display diagonal: 60.5 cm (23.8"), Display resolution: 1920 x 1080 pixels, HD type: Full HD, Display technology: LCD, Response time: 8 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black | Vendor Homepage: <https://www.dell.com/en-uk/shop/> | Anti-glare screen: Yes | Backlight type: LED | Contrast ratio (typical): 1500:1 | Dell ComfortView technology: Yes | Display brightness (typical): 250 | Display diagonal: 23.8 | Display number of colours: 16.7 million colours | Display resolution: 1920 x 1080 | Display technology: LCD | HD type: Full HD | Horizontal scan range: 30 - 110 | LED backlight: Yes | Maximum refresh rate: 100 | Native aspect ratio: 16:9 | Panel type: IPS | Pixel density: 92.53 | Pixel pitch: 0.2745 x 0.2745 | Response time: 8 | Response time (fast): 5 | Screen shape: Flat | sRGB coverage (typical): 99 | Supported graphics resolutions: 1024 x 768 (XGA)/1152 x 864 (XGA+)/1280 x 1024 (SXGA)/1280 x 720 (HD 720)/1600 x 900/1920 x 1080 (HD 1080)/640 x 480 (VGA)/720 x 400/800 x 600 (SVGA) | Supported video modes: 1080p/480p/576p/720p | Surface hardness: 3H | Touchscreen: No | Vertical scan range: 48 - 100 | Viewable size diagonal: 604.7 | Viewable size, horizontal: 527.04 | Viewable size, vertical: 296.46 | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | AMD FreeSync: No | Flicker-free technology: Yes | Low Blue Light technology: Yes | Mac operating systems supported: MacOS | NVIDIA G-SYNC: No | Windows operating systems supported: Windows 10/Yes | Built-in camera: No | Built-in speaker(s): No | Feet colour: Grey | Front bezel colour: Black | Product colour: Black | AC (power) in: Yes | Built-in USB hub: Yes | DisplayPort version: 1.4 | DisplayPorts quantity: 2 | HDCP: Yes | HDCP version: 1.4 | HDMI: Yes | HDMI ports quantity: 1 | HDMI version: 1.4 | Headphone out: No | Number of USB Type-C upstream ports quantity: 1 | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | USB Power Delivery (USB PD): Yes | USB Power Delivery up to: 90 | USB Type-A downstream ports quantity: 3 | USB Type-C DisplayPort Alternate Mode: Yes | USB Type-C downstream ports quantity: 1 | Adjustable height (max): 150 | Cable lock slot: Yes | Cable lock slot type: Kensington | Cable management: Yes | Height adjustment: Yes | LED indicators: Yes | On Screen Display (OSD): Yes | Panel mounting interface: 100 x 100 | Pivot: Yes | Pivot angle: -90 - 90 | Plug and Play: Yes | Swivel angle range: -45 - 45 | Swivelling: Yes | Tilt adjustment: Yes | Tilt angle range: -5 - 21 | VESA mounting: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 14 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): D | Energy efficiency scale: A to G | European Product Registry for Energy Labelling (EPREL) code: 1865677 | Input current: 2 | Power consumption (max): 180 | Power consumption (off): 0.3 | Power consumption (standby): 0.3 | Power consumption

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(typical): 13.9 | Power supply type: Internal | Non-operating altitude: 0 - 12192 | Operating altitude: 0 - 5000 | Operating relative humidity (H-H): 10 - 80 | Operating temperature (T-T): 0 - 40 | Storage relative humidity (H-H): 5 - 90 | Storage temperature (T-T): -20 - 60 | Bezel width (bottom): 12 | Bezel width (side): 5.8 | Bezel width (top): 5.8 | Depth (with stand): 181.75 | Depth (without stand): 50.03 | Height (with stand): 364 | Height (without stand): 314.23 | Weight (with stand): 5180 | Weight (without stand): 3690 | Width (with stand): 538.64 | Width (without stand): 538.64 | Package weight: 7240 | USB cable length: 1 | Cables included: AC/DisplayPort/USB Type-C | DisplayPort cable length: 1.8 | Quick start guide: Yes | Stand included: Yes | Doesn't contain: Arsenic/Mercury/PVC/BFR | Sustainability certificates: ENERGY STAR/TCO | Sustainability compliance: Yes | Carbon emissions, end-of-life (kg of CO2e): 2.688 | Carbon emissions, energy usage (kg of CO2e): 68.376 | Carbon emissions, logistics (kg of CO2e): 11.592 | Carbon emissions, manufacturing (kg of CO2e): 85.344 | PAIA version: GaBi version 1, 2024 | Total carbon footprint (kg of CO2e): 168 | Compliance certificates: RoHS/TÜV mark | RJ-45 ports quantity: 1 | Dell Display Manager (DDM) compatibility: Yes | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/1865677/fiches?language=EN> | Energy efficiency class: D | EPREL Registration Number: 1865677 | EPREL Version Number: 2 | Model: P2425HE | Unit Calculated Volume: 0.04112 | Product Net Weight: 5.44 | Unit Calculated Weight: 6.97