

CyberPower PDU20BHVIEC12R maitinimo paskirstymo įrenginys 12 AC išvestis(ys / čių) 1U Juoda

Gamintojas: **CYBERPOWER** · Modelis: **PDU20BHVIEC12R** · EAN: **4712364144387** · Prekės kodas: **504778**



140,90 €

Kaina su PVM

Be PVM: **116,45 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Vienfazis Pagrindinis 1U Juoda
- ✓ 12 AC išvestis(ys / čių) C13 šakotuvus
- ✓ Grandinės pertraukiklis



Aprašymas

The CyberPower 12-outlet (12 Rear) rack mount basic power distribution unit (PDU20BHVIEC12R) provides 208V/230V 20A output. It distributes power to 12 IEC-320 C13 receptacles from a single IEC-320 C20 plug, with unfiltered electrical pass-through. Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It can be mounted either horizontally or vertically, includes a cord retention tray and is ETL/RoHS certified. A lifetime warranty ensures that this PDU is free of defects in design, assembly, material or workmanship.

- 12 IEC-320 C13 output receptacles
- Single IEC-320 C20 plug
- 20-amp electrical capacity with circuit breaker
- 208/230V - 50/60Hz
- 1U rack mount
- 10-ft. power cord

Techninė specifikacija

Design	
PDU types	Basic
Rack capacity	1U
Type	Single-phase
Mounting	Horizontal/Vertical
Housing material	Steel
Product colour	Black
Ports & interfaces	
AC outlets quantity	12 AC outlet(s)
AC outlet types	C13 coupler
Power plug	C20 coupler
Features	
Cable length	3.05 m
Power	
Nominal input voltage	200 - 240 V
Maximum current	16 A
AC input frequency	50 / 60 Hz
Nominal output voltage	200 - 240 V
Power protection features	Overload
Surge protection	Yes
Circuit breaker	Yes
Certificates	
Compliance certificates	RoHS
Certification	UL60950_1 ETL, CSA C22.2
Operational conditions	
Operating temperature (T-T)	0 - 35 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m
Operating temperature (T-T)	32 - 95 °F

Weight & dimensions

Width	445 mm
Depth	38.1 mm
Height	44.5 mm
Weight	900 g
Weight (imperial)	0.907 kg (2 lbs)
Dimensions (W x D x H) (imperial)	444.5 x 38.1 x 44.5 mm (17.5 x 1.5 x 1.75")

Packaging content

Packaging content	PDU20BHVIEC12R, User's Manual, Product Registration Card, Cord Retention Tray, Mounting Brackets, Cable Ties, Screw Kit
-------------------	---

Packaging data

Package weight	15 kg
Package width	530 mm
Package depth	330 mm
Package height	233 mm

Logistics data

Warranty period	2 year(s)
-----------------	-----------

Sustainability

Sustainability compliance	Yes
---------------------------	-----