

Fujitsu Intel Xeon Silver 4210 processor 2.2 GHz 14 MB L3

Gamintojas: FUJITSU · Modelis: S26361-F4082-L110 · EAN: 4059595800348 · Prekės kodas: 505735



1 040,90 €

Kaina su PVM

Be PVM: 860,25 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Intel Xeon Silver 4210 2.2 GHz
- ✓ 14 MB L3 LGA 3647 (Socket P)
- ✓ Processor cores: 10 14 nm 64-bit 85 W
- ✓ Maximum internal memory supported by processor: 1 TB DDR4-SDRAM

Techninė specifikacija

Specifications

Sandėlio grupė

Komponenten & Zubehör > Prozessoren/CPUs [+337][-637]

Processor

Processor family	Intel Xeon Silver
Processor cores	10
Processor socket	LGA 3647 (Socket P)
Processor lithography	14 nm
Cooler included	No
Processor model	4210
Processor base frequency	2.2 GHz
Processor operating modes	64-bit
Processor generation	2nd Generation Intel® Xeon® Scalable
Component for	Server/workstation

Processor series	Intel Xeon Silver 4000 Series
Processor threads	20
Processor boost frequency	3.2 GHz
Processor cache	14 MB
Processor cache type	L3
Thermal Design Power (TDP)	85 W
Stepping	R1
Bus type	UPI
Processor codename	Cascade Lake
Memory	
Memory channels	Hexa-channel
Maximum internal memory supported by processor	1 TB
Memory types supported by processor	DDR4-SDRAM
Memory clock speeds supported by processor	2400 MHz
ECC	Yes
Graphics	
On-board graphics card	No
Discrete graphics card	No
Features	
Execute Disable Bit	Yes
Market segment	Server
Maximum number of PCI Express lanes	48
PCI Express slots version	3
Supported instruction sets	AVX-512
Scalability	25
Embedded options available	Yes
Processor special features	
Intel® Hyper Threading Technology (Intel® HT Technology)	Yes
Intel® Turbo Boost Technology	2
Intel® AES New Instructions (Intel® AES-NI)	Yes
Enhanced Intel SpeedStep Technology	Yes
Intel Trusted Execution Technology	Yes
Intel® Speed Shift Technology	Yes
Intel VT-x with Extended Page Tables (EPT)	Yes

Intel TSX-NI	Yes
Intel 64	Yes
Intel Virtualization Technology (VT-x)	Yes
Intel Virtualization Technology for Directed I/O (VT-d)	Yes
Intel Turbo Boost Max Technology 3.0	No
AVX-512 Fused Multiply-Add (FMA) units	1
Intel® Volume Management Device (VMD)	Yes
Mode-based Execute Control (MBE)	Yes
Intel® vPro™ Platform Eligibility	Yes
Operational conditions	
Tcase	78 °C
Logistics data	
Harmonized System (HS) code	85423119
Other features	
Compatibility	PRIMERGY TX2550 M5 PRIMERGY RX2540 M5
Technical details	
Intel® Run Sure Technology version	N
Number of UPI links	2