

Fujitsu Displays P2410 TS CAM.

Gamintojas: **FUJITSU** · Modelis: **S26361-K1699-V165** · EAN: **4065221160267** · Prekės kodas: **505751**



196,90 €

Kaina su PVM

Be PVM: **162,73 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 60.5 cm (23.8") Black
- ✓ Height adjustment 15 cm Built-in speaker(s)
- ✓ HDMI HDMI version: 1.4 DisplayPorts quantity: 2 DisplayPort version: 1.2
- ✓ Screen shape: Flat
- ✓ Response time: 5 ms
- ✓ 1920 x 1080 pixels Full HD Panel type: IPS
- ✓ Energy efficiency class (SDR): C



Aprašymas

The FUJITSU Display P2410 TS CAM is an IPS-based widescreen display that combines smart workplace concepts with advanced ergonomics. It comes with a multi-functional USB Type-C hub that makes it ideal for modern and shared workspaces. Multifunctional USB Type-C means:

- 95W power delivery for external devices.
- Transmission of video signals, webcam, data, LAN & audio.

It contains a Fujitsu patented solution that generates an All-In-One user experience with Mini PC ESPRIMO G and LIFEBOOK series.

The factory pre-calibrated display provides high color fidelity for single as multimonitor usage. KVM function reduces USB hardware needs by using one display for a number of devices.

For an easy log-in and professional video conferencing, the P2410 TS CAM comes with a Microsoft Windows HELLO compatible, bright Full HD Webcam with mechanical lever lock.

The directional microphone hides disturbing sounds. Fujitsu innovated the display housing by offering the worldwide first right-hand USB hub that

ensures an optimal cable course and is ergonomically perfect for most users.

Retina protection by low blue light panel that culls damaging blue light without any loss or changes of color.

The integrated Autobrightness sensor adapts the brightness of the display to an optimum, saves energy and increases constant productivity due to reduced eye strain.

DisplayView™ software enables you to configure your monitor easily for remote management and administrative tasks. Prolonged product lifecycle through feasible firmware updates done by the user.

Focusing on environmental friendliness, the packaging is styrofoam free and solely consisting of cardboard, which is more than 90% recycled.

Techninė specifikacija

Specifications	
Sandėlio grupė	Peripherie & Desktop > Monitore [+1613][-584]
Display	
Display diagonal	60.5 cm (23.8")
Display resolution	1920 x 1080 pixels
Native aspect ratio	16:9
Display technology	LED
Touchscreen	No
HD type	Full HD
Panel type	IPS
Response time	5 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Display brightness (typical)	250 cd/m²
Anti-glare screen	Yes
Supported graphics resolutions	640 x 480 (VGA), 800 x 600 (SVGA), 1024 x 768 (XGA), 1280 x 1024 (SXGA), 1280 x 720 (HD 720), 1440 x 900, 1680 x 1050 (WSXGA+)
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.2745 x 0.2745 mm
Viewable size, horizontal	52.7 cm
Viewable size, vertical	29.6 cm
Digital horizontal frequency	30 - 82 kHz
Digital vertical frequency	48 - 76 Hz
Colour gamut standard	sRGB
Colour gamut	99%
sRGB coverage (typical)	99%

Multimedia

Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W

Design

Product colour	Black
----------------	-------

Ports & interfaces

Built-in USB hub	Yes
HDMI	Yes
Headphone out	Yes
Number of upstream ports	2
Number of USB Type-B upstream ports quantity	1
Number of USB Type-C upstream ports quantity	1
USB Type-A downstream ports quantity	3
USB Type-C downstream ports quantity	1
HDMI ports quantity	1
HDMI version	1.4
DisplayPorts quantity	2
DisplayPort version	1.2
Headphone connectivity	3.5 mm
Built-in KVM switch	Yes

Network

Ethernet LAN	Yes
--------------	-----

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Height adjustment	Yes
Cable lock slot type	Kensington
Adjustable height (max)	15 cm
Swivelling	Yes
Swivel angle range	0 - 345°
Tilt adjustment	Yes
Tilt angle range	-5 - 35°

On Screen Display (OSD)	Yes
Power	
Energy efficiency class (SDR)	C
Energy consumption (SDR) per 1000 hours	12 kWh
Power consumption (max)	26 W
Power consumption (off)	0.26 W
Power consumption (PowerSave)	0.51 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Energy efficiency scale	A to G
Operational conditions	
Operating temperature (T-T)	5 - 35 °C
Operating relative humidity (H-H)	10 - 85%
Weight & dimensions	
Width (with stand)	539.1 mm
Depth (with stand)	212.7 mm
Height (with stand)	500.6 mm
Weight (with stand)	6 kg
Width (without stand)	539.1 mm
Depth (without stand)	59.2 mm
Height (without stand)	338.6 mm
Weight (without stand)	4.1 kg
Matmenys ir svoris	
Svoris	10,00kg