

APC SMC1500I-2UC nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 1,5 kVA 900 W 4 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMC1500I-2UC** · EAN: **731304332954** · Prekės kodas: **506407**



1 148,90 €

Kaina su PVM

Be PVM: **949,50 €**

Sandėlyje






Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 1,5 kVA 900 W
- ✓ Signalų forma: Sinusas
- ✓ 4 AC išvestis(ys / čių)
- ✓ Rūgštinis akumuliatorius (VRLA)
- ✓ Stelažas Juoda



Aprašymas

Stay always online and prevent data loss

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the free APC PowerChute software, you can even have critical IT hardware shut down automatically and in a controlled manner when the UPS battery is almost empty. This prevents data loss, downtime and physical damage to hardware.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is therefore ideally suited for (small) business use.

SmartConnect

Out-of-box remote UPS monitoring, free during a trial period of 6 months. Using the SmartConnect Ethernet port, you can easily connect the Smart-UPS to your network and you can easily monitor it remotely via the secure APC SmartConnect cloud-based web portal*. In addition, the UPS can always be monitored via this port via EcoStruxure IT Expert (SFTWES1-DIGI).

* Extend access to SmartConnect via the following licenses:

1 year Standard Plan: ERWPMON1-1Y-DIGI

3 years Standard Plan: ERWPMON1-3Y-DIGI

1 year Advanced Plan: ERWPLUS1-1Y-DIGI

3 years Advanced Plan: ERWPLUS1-3Y-DIGI

PowerChute

By connecting the UPS via a USB cable to a maximum of one server, it can automatically provide it with a shutdown signal during a long-term power failure and thus still prevent a hard shutdown. This exact moment can be set via the free APC PowerChute Serial Edition software.

Ease of use

The basic functionalities can be set and read out using physical buttons and an LCD screen. Thanks to the supplied front post brackets for rack mounting rail, you can easily mount the UPS in a rack.

Battery life

You can easily read the expected battery life in the runtime graph, which you can find between the product images. This way, you can easily see how long the UPS will provide emergency power at a certain load.

Extend the lifespan

The internal battery cartridge (APCRBC132) can be easily, safely and independently replaced by the user. This without having to switch off the APC SMC1500I-2UC or connected equipment. This way, you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment will always remain online.

Warranty extension

The factory warranty of the SMC1500I-2UC is 2 years and can be upgraded to 5 years with the APC service pack (WBEXTWAR3YR-SP-03).

This APC Smart-UPS is designed for small to medium business users to maintain business uptime and continuity. This 1500VA line interactive 2U rackmount UPS provides pure sine wave power to support critical electronics during power disruptions. The UPS comes with IEC 320 C14 input, 4x IEC 320 C13 outlets, and 2x IEC jumper cables. This UPS offers cloud-based remote power monitoring, UPS firmware upgrades, remote diagnostics and proactive email notifications with recommended actions. The Smart-UPS C has an intuitive graphic LCD interface. The UPS can connect to EcoStruxure IT or third-party centralized management platforms. This line interactive UPS operates in green mode for high operating efficiency. The SMC has built-in lead-acid battery and is covered by a 2-year UPS warranty. This UPS provides surge protection against lightning strikes, power sags,

brownouts and surges. This is compatible with a dedicated user-replaceable battery, and the APC replacement battery cartridge helps restore UPS performance to the original specifications.

Techninė specifikacija

Savybės	
UPS topologija	„Line-Interactive“
Išvesties galia (VA)	1,5 kVA
Išvesties galia	900 W
Signalų forma	Sinusas
Išvesties eksploatacinė įtampa (min.)	170 V
Išvesties eksploatacinė įtampa (maks.)	300 V
Išėjimo dažnis	50/60 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Išvesties dažnis	50/60 Hz
Automatinis įtampos reguliavimas (AVR)	Taip
Viršįtampio energijos įvertinimas	459 J
Išvesties įtampa THD	5%
Garso lygis	46 dB
Garsiniai perspėjimo signalai	Taip
Web pagrįstas valdymas	Taip
Garsinio pavojaus signalo režimai	Signalas veikiant su akumuliatoriumi, Senkančio akumuliatoriaus signalas, Perkrovos signalas
Automatinis paleidimas iš naujo	Taip
Temperatūros įtampos kompensavimas	Taip
Ryšys	
AC išėjimo tipai	C13 šakotuvai
Maitinimo laido kištukas	C14 šakotuvai
Lizų kiekis	4 AC išvestys(ys / čių)
USB prievadas	Taip
USB 2.0 portų kiekis	1
Nuoseklioji sąsaja	Taip
Nuosekliosios sąsajos tipas	RJ-45
„SmartSlot“	Ne
„SmartConnect“ prievadas	Taip

Baterija

Baterijos technologija	Rūgštinis akumulatorius (VRLA)
Baterijos veikimo trukmė (maks.)	6 metai
Baterijos įkrovimo laikas	3 h
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip
Aušinimo paleidimas	Taip

Konstrukcija

Forma	Stelažas
Produkto spalva	Juoda
Rėmo pajėgumas	2U
Ekrano tipas	LCD
LED indikatoriai	Taip

Aplinkos sąlygos

Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m

Sertifikatai

Sertifikavimas	C-tick, CE, CSA, GOST, UL 1778, VDE
----------------	-------------------------------------

Pakuotės turinys

Stovo montavimo rinkinys	Taip
Pridėti kabeliai	USB laidas
Pridedama valdymo kortelė	Ne
Greito diegimo vadovas	Taip

Tvarumas

Tvarumo sertifikatai	Green Premium
----------------------	---------------

Svoris ir matmenys

Plotis	432 mm
Ilgis	477 mm
Aukštis	86 mm
Svoris	28,6 kg

Pakuotės duomenys

Šaltinis CD	Taip
Programinės įrangos CD	Taip
Pakuotės plotis	594 mm
Pakuotės gylis	603 mm
Pakuotės aukštis	251 mm
Paketo svoris	31,9 kg

Logistikos duomenys

Gaminių skaičius ant padėklo	16 vnt
Darniosios sistemos (DS) kodas	85078000
Bendras anglies pėdsakas (kg of CO2e)	1363,77

Matmenys ir svoris

Matmenys (I × P × A)	61,00cm × 60,00cm × 24,00cm
Svoris	29,40kg

Dokumentai ir vaizdo įrašai

[› Naudojimo instrukcija](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

[se.com](https://www.se.com)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

info@shopro.lt