APC Smart-UPS nepertraukiamo maitinimo resursai (UPS) „Line-Interactive“ 1,5 kVA 1200 W 8 AC išvestis(ys / čių)

Gamintojas: **APC** · Modelis: **SMX1500RMI2U** · EAN: **731304268598** · Prekės kodas: **506641**



2 040,89 €

Kaina su PVM

Be PVM: **1 686,69 €**

Sandėlyje


Prekė internetu

Nuskenuokite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ „Line-Interactive“
- ✓ 1,5 kVA 1200 W
- ✓ Signalų forma: Sinusas
- ✓ 8 AC išvestis(ys / čių)
- ✓ Rūgštinis akumuliatorius (VRLA)
- ✓ Stelažas / bokštas Juoda













Aprašymas

Always stay online and prevent data loss

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

As soon as the power fails, an APC Smart-UPS immediately supplies emergency power to all connected equipment. Because an APC UPS does this automatically, you prevent unwanted failure of, for example, a PC, server or switch. With the free APC PowerChute software, you can even have critical IT hardware shut down automatically and in a controlled manner when the UPS battery is almost empty. This prevents data loss, downtime and physical damage to hardware.

Extend the runtime

You can easily increase the number of minutes that the APC SMX UPS can independently supply emergency power by connecting external battery packs (SMX48RMBP2U).
A runtime of several hours is even possible.

Safety

In addition, a Smart-UPS protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for (small) business use.

Network Management Card

If you connect the UPS directly to your network via the optional APC Network Management Card (AP9640/AP9641), it can be easily managed remotely via SNMP or our remote management software Ecostruxure IT Expert (SFTWES1-DIGI). You can also automatically send a shutdown signal via the network to multiple physical and/or virtual servers. By means of the APC PowerChute Network Shutdown Software belonging to the network card, it is even possible to differentiate between the shutdown moment and the order in which this happens.

Easy to use

This APC Smart-UPS SMX is easy to operate thanks to the LCD screen.

Rack/tower convertible

The APC Smart-UPS SMX is rack/tower convertible. Because both the feet and the 4 post rack mounting brackets are included, you can mount it in a rack (2U) or place it upright.

Extend the lifespan

The internal battery cartridge (APCRBC115) can be replaced easily, safely and independently by the user. This without having to switch off the APC SMX1500RMI2U or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always stays online.

Warranty extension

The factory warranty of the SMX1500RMI2U is 3 years, with the exception of the battery cartridge, which has a factory warranty of 2 years. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-03).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which can limit oversizing of the UPS.

It is also possible to reset a group of multiple UPS outputs and the equipment connected to them. If a network card (ap9640) is used in combination with Ecostruxure IT Expert (SFTWES1-DIGI), this can even be done remotely.

You can also switch off non-critical loads; this extends the runtime for critical equipment.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

This APC Smart-UPS is designed for IT managers or network administrators to maintain business uptime, data transfer and continuity during prolonged power outages. The 1500VA line interactive 2U rack/tower UPS provides pure sine wave power to support critical electronics during power disruptions. The SMX comes with IEC 320 C14 input, 8x IEC 320 C13 outlets, and 2x IEC jumper cables. The UPS has a SmartSlot for optional Network Management Card that enables graceful shutdown of physical servers, virtual machines & HCI Clusters via PowerChute Network Shutdown. It comes with IEC 320 C14 input, 8x IEC 320 C13 outlets, and 2x IEC jumper cables. The UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. This uninterrupted power supply can connect to EcoStruxure IT or third-party centralized management platforms. The SMX UPS has a 3-year warranty, and the built-in lead-acid battery has a 2-year warranty. This is compatible with dedicated user-replaceable battery, and the APC replacement battery cartridge helps restore UPS performance to the original specifications. The Smart-UPS comes with a pair of tower-mounting stabilizing feet and rack-mounting brackets. The 3 switchable outlet groups allow more granular management of the power supplied to your devices. The Emergency Power Off feature enables the UPS to remotely shutdown during emergencies.

Techninė specifikacija

Features	
UPS topology	Line-Interactive
Output power capacity	1.5 kVA
Output power	1200 W
Waveform	Sine
Input operation voltage (min)	151 V
Input operation voltage (max)	302 V
Input frequency	50/60 Hz
Output frequency regulation	50/60 Hz
Automatic Voltage Regulation (AVR)	Yes
Surge energy rating	645 J
Efficiency	98.5%
Emergency Power Off (EPO)	Yes
Noise level	40 dB
Audible alarm(s)	Yes
Audible alarm modes	Low battery alarm, Overload alarm
Auto-restart	Yes
Ports & interfaces	
AC outlet types	C13 coupler
Power plug	C14 coupler
AC outlets quantity	8 AC outlet(s)
Number of output IEC jumpers	2
USB port	Yes
Ethernet LAN (RJ-45) ports	0
SmartSlot	Yes

SmartConnect port	No

Battery

Battery technology	Sealed Lead Acid (VRLA)
Battery capacity	311 VAh
Typical backup time at full load	5.8 min
Typical backup time at half load	17.2 min
Battery life (max)	5 year(s)
Battery recharge time	3 h
Hot-swap battery	Yes
Automatic battery test	Yes
Cold start	Yes

Design

Form factor	Rackmount/Tower
Product colour	Black
Rack capacity	2U
Cable length	1.83 m
LED indicators	Yes

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 45 °C
Operating relative humidity (H-H)	0 - 95%
Storage relative humidity (H-H)	0 - 95%
Operating altitude	0 - 3000 m
Non-operating altitude	0 - 15000 m

Certificates

Compliance certificates	RoHS
Certification	CE, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOLI

Packaging content

Rack mount kit	Yes
Cables included	RS-232, USB cable
Management card included	No
Quick installation guide	Yes

Weight & dimensions

Width	432 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt · info@shopro.lt · +370 693 39903

Depth	490 mm
Height	89 mm
Weight	24.8 kg
Packaging data	
Software CD	Yes
Package width	589 mm
Package depth	620 mm
Package height	246 mm
Package weight	30 kg
Logistics data	
Products per pallet	8 pc(s)
Harmonized System (HS) code	85078000
Total carbon footprint (kg of CO2e)	1419.64
Other features	
Nominal output voltage	230 V
Nominal input voltage	230 V
Packaging content	Removable support feet
Matmenys ir svoris	
Matmenys (I × P × A)	63,00cm × 59,00cm × 25,00cm

Dokumentai ir vaizdo įrašai

- Naudojimo instrukcija
- Gaminio lankstinukas

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE
rue Joseph Monier 35, 92500 Rueil Malmaison, FR
se.com

PLATINTOJAS

MB KOMPIUTERIŲ GURU
V. Nagevičiaus g. 3, LT-08237 Vilnius
info@shopro.lt

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.