

iiyama ProLite T1932MSC-B1S kompiuterio monitorius 48,3 cm (19") 1280 x 1024 pikseliai „Full HD“ LED Lietimui jautrus ekranas Stalo paviršius Juoda

Gamintojas: **IIYAMA** · Modelis: **T1932MSC-B1S** · EAN: **4948570122196** · Prekės kodas: **507163**



655,90 €

Kaina su PVM

Be PVM: **542,07 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ 48,3 cm (19") Juoda
- ✓ Įmontuoti garsiakalbiai
- ✓ HDMI „DisplayPort“ kiekis: 1
- ✓ Ekranas: Plokščias
- ✓ Reakcijos laikas: 14 ms Atsako trukmės matavimo tipas: GTG (Gray to Gray)
- ✓ 1280 x 1024 pikseliai „Full HD“ Skydo tipas: IPS
- ✓ Energijos vartojimo efektyvumo klasė (SDR): E ErP CE, cULus, EAC, REACH, RoHS, UKCA, WEEE



Aprašymas

The ProLite T1932MSC-B1S 19" 10tp touchscreen is based on projective capacitive technology which thanks to a glass overlay covering the screen guarantees high durability, scratch-resistance and perfect picture performance. The IPS panel guarantees high performance with accurate and consistent colour reproduction, and wide viewing angles. Its touch function remains unaffected even if the glass is scratched. A solid and steady base supports the touchscreen with an adjustable stand offering full 90 degree positioning angles. In addition, the edge-to-edge glass design creates an eye-catching finish with high light transmission guaranteeing perfect picture clarity and brilliant colours.

Techninė specifikacija

Display	
Display diagonal	48.3 cm (19")
Display resolution	1280 x 1024 pixels
Native aspect ratio	5:4
Display technology	LED
Touchscreen	Yes
HD type	Full HD
Panel type	IPS
Response time	14 ms
Screen shape	Flat
Contrast ratio (typical)	1000:1
Display number of colours	16.7 million colours
Backlight type	LED
Touchscreen type	Tabletop
Touchscreen technology	Projected capacitive system
Touch technology	Multi-touch
Number of simultaneous touchpoints	10
Display brightness (peak)	215 cd/m²
Display brightness (typical)	250 cd/m²
Display brightness	225 cd/m²
Response time measurement type	GTG (Gray to Gray)
Display surface	Matt
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Pixel pitch	0.2928 x 0.2928 mm
Horizontal scan range	31 - 80 kHz
Viewable size, horizontal	37.5 cm
Viewable size, vertical	30 cm
Display diagonal (metric)	48 cm
DDC/CI	Yes
Performance	
NVIDIA G-SYNC	No
AMD FreeSync	No

Multimedia

Built-in speaker(s)	Yes
Built-in camera	No
Number of speakers	2
RMS rated power	2 W

Design

Market positioning	Business
Product colour	Black
Front bezel colour	Black
Feet colour	Black

Ports & interfaces

Built-in USB hub	No
HDMI	Yes
USB Touch port	Yes
VGA (D-Sub) ports quantity	1
HDMI ports quantity	1
DisplayPorts quantity	1
Audio input	Yes
Audio output	Yes
Headphone outputs	1
HDCP	Yes
DC-in jack	Yes

Ergonomics

VESA mounting	Yes
Cable lock slot	Yes
Panel mounting interface	100 x 100 mm
Cable management	Yes
Cable lock slot type	Kensington
Tilt adjustment	Yes
Tilt angle range	5 - 90°
On Screen Display (OSD)	Yes
On Screen Display (OSD) languages	Traditional Chinese, German, English, Spanish, French, Italian, Japanese
Number of OSD languages	7

Power

Energy efficiency class (SDR)	E
Energy efficiency class (HDR)	Not available
Energy consumption (SDR) per 1000 hours	13.4 kWh
Power consumption (typical)	20 W
Power consumption (standby)	1.5 W
Power consumption (off)	0.3 W
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Power supply type	Internal
Energy efficiency scale	A to G
Weight & dimensions	
Width (with stand)	432 mm
Depth (with stand)	239.5 mm
Height (with stand)	413.5 mm
Weight (with stand)	5.4 kg
Packaging content	
Stand included	Yes
Cables included	AC, USB, HDMI, DisplayPort
Power adapter included	Yes
Quick start guide	Yes
Manual	Yes
Sustainability	
Sustainability certificates	ErP
Sustainability compliance	Yes
Other features	
International Protection (IP) code	IP54
Compatible operating systems	All iiyama monitors are Plug & Play and compatible with Windows and Linux. For details regarding the supported OS for the touch models, please refer to the driver instruction file available in the downloads section.
Brightness	225 cd/m²
Active display area (W x H)	374.8 x 300 mm
Weight	5.4 kg
Height	413.5 mm
Width	432 mm
Depth	239.5 mm

Compliance certificates	CE, cULus, EAC, REACH, RoHS, UKCA, WEEE
Mean time between failures (MTBF)	50000 h
User controls	Picture (contrast, brightness, H.position, V.position, phase, clock, auto adjust), advanced (color temp., sharpness), OSD (timeout, position, H-position, V-position), option (reset, language, source select, display mode, volume, factory)
Touch method	stylus, finger, glove
Control panel	Menu, Scroll up/ Brightness, Scroll down/ Mute, Select, Power