

Vivolink VLHDMIMAT4X444-R AV extender AV receiver Black

Gamintojas: **VIVOLINK** · Modelis: **VLHDMIMAT4X444-R** · EAN: **5704174240556** · Prekės kodas: **508334**



420,90 €

Kaina su PVM

Be PVM: **347,85 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Supports HDMI 2.0 and the HDMI video resolution up to 4K@60Hz 4:4:4 HDR.
- ✓ Bidirectional IR, RS232 and 24V PoC.
- ✓ SPDIF out on receiver for source audio de-embedding.



Aprašymas

VLHDMIMAT4X444-R HDMI 2.0 receiver which is designed to receive 4K video from transmitter at distance up to 131 feet (40 meters) and 1080P video at distances up to 230 feet (70 meters) over a single CATx cable.

It supports audio de-embedded and ARC.

It also supports bidirectional IR and RS232 pass-through to control source or display device remotely. PoC feature allows the transmitter and the receiver can be powered from each other and only one power adapter is needed in system.

Techninė specifikacija

Specifications

Sandėlio grupė

Komponenten & Zubehör > Gehäuse [+1073][-10667]

Features

Type	AV receiver
Maximum resolution	4096 x 2160 pixels
Maximum transfer distance	70 m
High Dynamic Range (HDR) supported	Yes
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)
Bidirectional	Yes
CEC pass-through	Yes
LED indicators	Yes
Bandwidth	18 Gbit/s
Audio formats supported	PCM
HDCP	Yes
Consumer Electronics Control (CEC) support	Yes
Signal-to-Noise Ratio (SNR)	85 dB
HDCP version	1.4/2.2
Product colour	Black
HDBaseT certified	Yes
Ports & interfaces	
Connectivity technology	Wired
Ethernet LAN	Yes
RJ-45 input ports	1
HDBaseT port	Yes
Number of HDMI outputs	1
HDMI version	2
USB ports quantity	1
USB version	2
USB connector type	Micro-USB
RS-232 input ports	1
Digital audio optical in	1
Digital audio optical input type	TOSLINK
Digital audio optical out	1
Audio (L/R) out	4
Audio input	1
Audio output	1
3.5 mm (1/8-inch) in	Yes
3.5 mm (1/8-inch) out	Yes

Remote (IR) input	1
Remote (IR) output	1
Power	
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Output current	1.25 A
Operating voltage (receiver)	24 V
Power consumption (receiver) (max)	12 W
Operational conditions	
Operating temperature (T-T)	-5 - 55 °C
Storage temperature (T-T)	-25 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Weight & dimensions	
Width	140 mm
Depth	84 mm
Height	19.5 mm
Weight	400 g
Packaging data	
Quantity per pack	1 pc(s)
Package weight	610 g