

Conceptronic ZEUS03G 1200VA 720W UPS, UK socket x 4, HID USB, RJ45 In/Out, AVR

Gamintojas: **CONCEPTRONIC** · Modelis: **ZEUS03G** · EAN: **4015867241455** · Prekės kodas: **509212**



182,90 €

Kaina su PVM

Be PVM: **151,16 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Built-in AVR protects against voltage fluctuation
- ✓ DC Start
- ✓ Powerful microprocessor design
- ✓ Modem / LAN Internet protection
- ✓ AC auto restart
- ✓ Provides HID compatible USB connection



Aprašymas

The Conceptronic UPS provides long-lasting, reliable battery backup for the home or small office. The unit is simple to install and operate, offering an easy and safe way of protecting your systems from harmful power surges and failures. The UPS comes with modem/LAN protection, a powerful microprocessor and a fault indicator which warns against dangerous wiring. Stylish, compact design makes the UPS ideal for limited office and home working spaces.

Techninė specifikacija

Specifications

Sandėlio grupė

Stromversorgung > USV [+474][-335]

Features

UPS topology	Line-Interactive
Output power capacity	1.2 kVA
Output power	720 W
Input operation voltage (min)	220 V
Input operation voltage (max)	240 V
Output operation voltage (min)	220 V
Output operation voltage (max)	240 V
Automatic Voltage Regulation (AVR)	Yes
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Fault, Low battery alarm, Overload alarm
Auto-restart	Yes
Socket circuit breaker	Yes

Ports & interfaces

AC outlet types	Type G (BS 1363)
AC outlets quantity	4 AC outlet(s)
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Ethernet LAN (RJ-45) ports	2

Battery

Battery technology	Lead-Acid
Battery capacity	14 Ah
Battery voltage	24 V
Number of batteries supported	2
Battery recharge time(90%)	8 h
Battery capacity	168 Wh

Design

Form factor	Desktop
Product colour	Black
Display type	LCD
LED indicators	Yes
International Protection (IP) code	IP20

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	0 - 90%
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	USB cable
Quick installation guide	Yes
Weight & dimensions	
Width	148 mm
Depth	298 mm
Height	178 mm
Weight	7.6 kg
Packaging data	
Package width	255 mm
Package depth	376 mm
Package height	268 mm
Package weight	8.24 kg
Logistics data	
Pallet gross length	80 cm
Pallet gross width	120 cm
Pallet gross height	2.04 m
Harmonized System (HS) code	8504406090
Master (outer) case width	272 mm
Master (outer) case length	397 mm
Master (outer) case height	293 mm
Master (outer) case gross weight	8.81 kg
Products per master (outer) case	1 pc(s)
Country of origin	China