

Conceptronic ZEUS51E6K 6000VA 6000W Online Rack/Tower UPS

Gamintojas: **CONCEPTRONIC** · Modelis: **ZEUS51E6K** · EAN: **4015867237816** · Prekės kodas: **509224**



1 655,90 €

Kaina su PVM

Be PVM: **1 368,51 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Output power factor 1.0
- ✓ ECO mode for energy saving
- ✓ Wide Input Range (80V-300V)
- ✓ Generator compatible
- ✓ Provides HID compatible USB connection
- ✓ Emergency Power Off (EPO) port
- ✓ Easy battery replacement
- ✓ THDi≤5%
- ✓ Outlet programmable management
- ✓ Battery extendable



Aprašymas

The Conceptronic Online Rack/Tower UPS is the ultimate solution for dependable battery backup in both home and office settings. With an output power factor of 1.0, this UPS delivers maximum efficiency and performance. Its ECO mode feature conserves energy, making it an environmentally friendly choice. Designed for generator compatibility, it provides continuous power even during extended outages.

Equipped with a HID-compatible USB connection for seamless device communication and an Emergency Power Off (EPO) port for added safety during emergencies, the Conceptronic Online Rack/Tower UPS offers both convenience and security. The easy battery replacement feature simplifies maintenance, while the programmable outlet management allows you to tailor power distribution to meet your specific needs.

Easy to install and operate, the Conceptronic Online UPS provides a reliable and efficient way to protect your systems from power surges and failures, ensuring the uninterrupted operation of your critical equipment. The included rackmount ears support both rack mounting and tower

installation, offering flexibility in setup.

Techninė specifikacija

Specifications	
Sandėlio grupė	Stromversorgung > USV [+474][-335]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	6 kVA
Output power	6000 W
Waveform	Sine
Input operation voltage (min)	80 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output power factor	1
ECO mode	Yes
Input current Total Harmonic Distortion (THD)	5%
Audible alarm(s)	Yes
Audible alarm modes	Alarm when on battery, Battery replacement, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
USB port	Yes
USB 2.0 ports quantity	1
USB port type	USB Type-B
Serial interface	Yes
Serial interface type	RS-232
Serial ports quantity	1
Emergency Power Off (EPO) connector	Yes
Battery	
Battery capacity	7 Ah
Battery voltage	192 V
Number of batteries supported	16
Battery recharge time	4 h
Battery capacity	84 Wh

Design

Form factor	Rackmount/Tower
Product colour	Black
Display type	LCD

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-15 - 50 °C
Operating relative humidity (H-H)	0 - 90%

Certificates

Compliance certificates	CE, RoHS
-------------------------	----------

Weight & dimensions

Width	438 mm
Depth	480 mm
Height	131 mm
Weight	59.4 kg

Packaging data

Package type	Box
--------------	-----

Logistics data

Pallet gross length	57.5 cm
Pallet gross width	89.5 cm
Pallet gross height	126 cm
Customs product code (TARIC)	8504406090
Harmonized System (HS) code	850440
Master (outer) case width	570 mm
Master (outer) case length	890 mm
Master (outer) case height	572 mm
Master (outer) case gross weight	66 kg
Products per master (outer) case	1 pc(s)
Country of origin	China