

APC Smart-UPS On-Line SRT nepertraukiamo maitinimo resursai (UPS) Dviguba konversija (prisijungus) 3 kVA 2700 W

 Gamintojas: **APC** · Modelis: **SRT3000RMXLI** · EAN: **731304317647** · Prekės kodas: **513783**


3 737,90 €

Kaina su PVM

 Be PVM: **3 089,17 €**


Sandėlyje


Prekė internetu

 Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Dviguba konversija (prisijungus)
- ✓ 3 kVA 2700 W
- ✓ Signalų forma: Sinusas
- ✓ Rūgštinis akumulatorius (VRLA)
- ✓ Stelažas Juoda



Sustainable by Design



Energy Efficient Transparency RoHS/REACH



Aprašymas

Stay always online and prevent data loss

An APC Smart-UPS On-Line always supplies perfectly clean power to all connected equipment thanks to its double conversion technology. Even power outages have no influence on this. The APC Smart-UPS On-Line then automatically supplies emergency power without having to switch. This way you prevent unwanted failure of, for example, a PC, server, storage or switch. With the free APC PowerChute software you can even have critical IT hardware shut down automatically and in a controlled manner when the battery of the UPS is almost empty. This way you prevent data loss, downtime and physical damage to hardware.

Extend the runtime

You can easily increase the number of minutes that the APC SRT3000RMXLI can independently supply emergency power by connecting external battery packs (SRT96RMBP). A runtime of several hours is even possible.

Availability

The Smart-UPS On-Line has an internal bypass and uses double conversion, maximizing the availability and lifespan of connected hardware. It also makes the UPS compatible with an emergency power generator. The Un-Line double conversion technology ensures clean, uninterrupted power to protected equipment even when generator power is used.

Safety

In addition, a Smart-UPS On-Line protects connected devices against peak voltage caused by lightning, among other things. This APC emergency power supply is ideally suited for business use.

Ease of use

The APC Smart-UPS SRT is easy to operate thanks to a tilting graphic LCD screen and physical buttons. This makes it possible to set and read the basic functionalities. Because the background color of the screen changes depending on the type of warning, the severity of the situation can be quickly visually assessed. Thanks to the included 4-post rail kit, you can easily mount the UPS in a rack.

Network Management Card

If you connect the UPS directly to your network via the optional APC Network Management Card (AP9640/AP9641), it can easily be managed remotely via SNMP or our remote management software Ecostruxure IT Expert (SFTWES1-DIGI). You can also automatically send a shutdown signal via the network to multiple physical and/or virtual servers. By means of the APC PowerChute Network Shutdown Software associated with the network card can even be differentiated in the shutdown moment and the order in which this happens.

Extend the lifespan

The internal battery cartridge (APCRBC152) can be replaced easily, safely and independently by the user. This without having to switch off the APC SRT3000RMXLI or connected equipment. This way you can easily and cheaply extend the lifespan of the APC Smart-UPS and your equipment always remains online.

Warranty extension

The manufacturer's warranty of the SRT3000RMXLI is 3 years, with the exception of the battery cartridge, which has a 2-year manufacturer's warranty. Both are extended by 3 years to 6 and 5 years respectively with the APC service pack (WBEXTWAR3YR-SP-04).

Switched Outlet Groups: Remote reboot and phased start-up

Thanks to the Switched Outlet Groups, it is possible to configure a phased/delayed power-on per UPS outlet group. This reduces the peak load on the UPS and brings it closer to the constant load, which limits oversizing of the UPS.

It is also possible to reset a group of multiple UPS outputs and the equipment connected to them. If a network card (ap9640) is used in combination with Ecostruxure IT Expert (SFTWES1-DIGI), this can even be done remotely.

You also cannot eliminate critical loads; This way you extend the runtime for critical equipment.

Green Premium

This label represents Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises to comply with the latest regulations, transparency on environmental effects and circular and low CO2 emission products.

Green Premium:

- Stands for an energy-efficient product that helps our customers achieve their CO2 reduction goals and save energy costs at the same time. The energy efficiency of this product is at least 10% higher than the market average.

- Provides insight into the environmental effects of the product, this data is available 24/7 via the digital product environmental profile, see <https://checkaproduct.se.com/>

- Commits to minimal use of hazardous substances within and beyond regulatory compliance (RoHS/REACH)

Included in the box

1x SRT3000RMXLI

1x USB cable

1x C13 to C14 power cord 1.2M

1x Software CD with Powershute Business Edition

1x Documentation CD

1x Schuko to C19 input power cord 2M

1x British BS1363A to C19 input power cord

1x C19 to C20 input power cord 2.5M

2x Rack mounting brackets

Techninė specifikacija

Savybės	
UPS topologija	Dviguba konversija (prisijungus)
Išvesties galia (VA)	3 kVA
Išvesties galia	2700 W
Signalų forma	Sinusas
Išvesties eksploatacinė įtampa (min.)	100 V
Išvesties eksploatacinė įtampa (maks.)	275 V
Įėjimo dažnis	40 - 70 Hz
Išvesties darbinė įtampa (min.)	220 V
Išvesties darbinė įtampa (maks.)	240 V
Išvesties dažnis	50/60 Hz
Automatinis įtampos reguliavimas (AVR)	Taip

Viršįtampio energijos įvertinimas	340 J
Efektyvumas	92%
Amplitudės koeficientas	3:1
Avarinis elektros išjungimas (EPO)	Taip
Išvesties įtampa THD	2%
Garso lygis	55 dB
Apsauga nuo viršįtampių	Taip
Maitinimo apsaugos ypatybės	Apsauga nuo perkrovos
Garsiniai perspėjimo signalai	Taip
Garsinio pavojaus signalo režimai	Baterijos keitimas
Automatinis paleidimas iš naujo	Taip

Ryšys

AC išėjimo tipai	C13 šakotuvus, C19 šakotuvus
Maitinimo laido kištukas	C20 šakotuvus
USB prievadas	Taip
Nuoseklioji sąsaja	Taip
Nuosekliosios sąsajos tipas	RJ-45
„SmartSlot“	Taip
„SmartConnect“ prievadas	Ne

Baterija

Baterijos technologija	Rūgštinis akumuliatorius (VRLA)
Baterijos talpa	505 VAh
Tipiško laikino maitinimo trukmė pilna apkrova	4 min
Tipiško laikino maitinimo trukmė pusei apkrovimo	11,8 min
Baterijos veikimo trukmė (maks.)	5 metai
Baterijos įkrovimo laikas	3 h
Hot-Swap baterija	Taip
Automatinis baterijos bandymas	Taip
Aušinimo paleidimas	Taip

Konstrukcija

Forma	Stelažas
Produkto spalva	Juoda
Rėmo pajėgumas	2U
Kabelio ilgis	2,44 m
Ekrano tipas	LCD

LED indikatoriai	Baterijos keitimas
Tarptautinės apsaugos (IP) kodas	IP20
Aplinkos sąlygos	
Darbo temperatūros diapazonas (TT)	0 - 40 °C
Sandėliavimo temperatūros norma (T-T)	-15 - 45 °C
Darbo santykinės drėgmės diapazonas	0 - 95%
Sandėliavimo santykinis drėgmės diapazonas	0 - 95%
Darbinis aukštis	0 - 3000 m
Ne darbinis aukštis	0 - 15000 m
Sertifikatai	
Atitikties sertifikatai	RoHS
Sertifikavimas	CE, VDE, RCM, EAC, IEC/EN 62040-1, IEC/EN 62040-2, UL-1778, FCC 15 A, CSA
Pakuotės turinys	
Pridedama valdymo kortelė	Ne
Greito diegimo vadovas	Taip
Svoris ir matmenys	
Plotis	432 mm
Ilgis	635 mm
Aukštis	85 mm
Svoris	31,3 kg
Pakuotės duomenys	
Pakuotės plotis	599 mm
Pakuotės gylis	871 mm
Pakuotės aukštis	246 mm
Paketo svoris	39,3 kg
Logistikos duomenys	
Gaminių skaičius ant padėklo	6 vnt
Darniosios sistemos (DS) kodas	85078000
Bendras anglies pėdsakas (kg of CO2e)	4993,35
Kitos savybės	
Išėjimo įtampa	230 V
Matmenys ir svoris	
Matmenys (I × P × A)	88,00cm × 60,00cm × 25,00cm
Svoris	39,91kg

Dokumentai ir vaizdo įrašai

> [Gaminio lankstinukas](#)

Gamintojo ir saugos informacija

GAMINTOJAS

Schneider Electric SE

rue Joseph Monier 35, 92500 RUEIL MALMAISON, FR

[se.com](#)

PLATINTOJAS

MB KOMPIUTERIŲ GURU

V. Nagevičiaus g. 3, LT-08237 Vilnius

[info@shopro.lt](#)