

Sharp MultiSync M502 Digital signage flat panel 127 cm (50") LCD 550 cd/m² 4K Ultra HD Black 24/7

Gamintojas: **SHARP** · Modelis: **PNM502** · EAN: **4550556131032** · Prekės kodas: **514922**



1 419,90 €

Kaina su PVM

Be PVM: **1 173,47 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Seamless meeting workflows – a single USB-C cable transmits video, data, and power for instant, clutter-free meeting setups. As the established standard for modern collaboration spaces, USB-C supports frictionless BYOD experiences.
- ✓ Unhindered readability – a high-haze panel reduces glare from windows and ambient light, keeping signage content and presentations clear for uninterrupted viewing in any environment
- ✓ Security assured – 802.1x support over LAN enables high-level security for corporate networks, giving peace of mind for IT teams and enterprise environments.
- ✓ Enhanced imaging precision – when brand consistency and corporate identity are important, NEC's SpectraView Engine provides full control over colour, gamma, and uniformity for accurate and impactful content.
- ✓ Broad AV compatibility – fully interoperable with leading meeting room platforms including Crestron (XiO Cloud), Cisco Webex, Q-Sys, and Microsoft Teams, ensuring effortless integration and future-proof scalability.



Aprašymas

Built to perform, designed to last

The versatile solution for professional display applications, the Sharp MultiSync® M2 Series (32" up to 98") is purpose-built for demanding signage and meeting room environments. With native USB-C connectivity and broad compatibility with platforms such as Crestron, Cisco Webex, and

Microsoft Teams, it enables seamless BYOD collaboration and future-ready integration, while 802.1x LAN support ensures enterprise-grade network security. Featuring class-leading 550 cd/m² brightness, a high-haze panel to minimise glare, and NEC's trusted SpectraView Engine, the M2 Series delivers outstanding visual performance with unmatched colour precision.

As part of the new Sharp-branded display family, the MultiSync® M2 Series builds on NEC's legacy of quality and reliability to drive greater efficiency and long-term value. Its proven modular design supports custom computing options (Raspberry Pi or Intel® SDM) and flexible connectivity (e.g. AV-over-IP), ensuring lasting versatility, performance, and sustainability.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Large Format [+87][-114]
Display	
Display diagonal	127 cm (50")
Display technology	LCD
Display resolution	3840 x 2160 pixels
Display brightness	550 cd/m ²
HD type	4K Ultra HD
Touchscreen	No
Panel type	VA
LED backlight	Yes
LED backlighting type	Direct-LED
Native aspect ratio	16:9
Contrast ratio (typical)	8000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	1.073 billion colours
Pixel pitch	0.285 x 0.285 mm
Active display area (W x H)	1095.8 x 616.4 mm
Display diagonal (metric)	125.7 cm
Maximum frame rate	60 fps
Haze rate	25%
RGB colour space	NTSC
Ports & interfaces	
HDMI ports quantity	3
DVI port	No
DisplayPorts quantity	2
USB port	Yes

HDMI input ports quantity	2
HDMI output ports quantity	1
DisplayPorts in	1
DisplayPorts out	1
USB ports quantity	4
USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
USB connector type	USB Type-A, USB Type-C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB Power Delivery (USB PD)	Yes
USB Power Delivery up to	65 W
Ethernet LAN (RJ-45) ports	2
RS-232C	Yes
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	20 W
Design	
Product design	Digital signage flat panel
Product colour	Black
VESA mounting	Yes
Panel mounting interface	300 x 300 mm
Bezel width (bottom)	1.39 cm
Bezel width (side)	1.09 cm
Bezel width (top)	1.09 cm
Performance	
Operating hours (hours/days)	24/7
International Protection (IP) code	IP5X, IP2X
Power	
Power consumption (typical)	85 W
Power consumption (standby)	2 W
Power consumption (off)	0.5 W
Energy efficiency class (SDR)	G
Energy consumption (SDR) per 1000 hours	81 kWh
AC input voltage	100 - 240 V

AC input frequency	50/60 Hz
Energy efficiency scale	A to G
Computer system	
Computer system	No
Built-in processor	No
Weight & dimensions	
Display width	1121.6 mm
Display depth	66.5 mm
Display height	645.2 mm
Display weight	18 kg
Packaging data	
Package width	1245 mm
Package depth	188 mm
Package height	785 mm
Package weight	23 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	20 - 80%
Network	
Ethernet LAN	Yes
Ethernet LAN data rates	10,100 Mbit/s
Features	
Base material	Metal
Matmenys ir svoris	
Matmenys (I × P × A)	124,00cm × 78,00cm × 19,00cm
Svoris	25,40kg