

CyberPower OLS3000EA-DE uninterruptible power supply (UPS) Double-conversion (Online) 3 kVA 2700 W 7 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OLS3000EA-DE** · EAN: **4711027790251** · Prekės kodas: **515416**



586,90 €

Kaina su PVM

Be PVM: **485,04 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Surge and Spike Protection
- ✓ Color LCD Panel
- ✓ Serial Connectivity Port
- ✓ PowerPanel® Management Software
- ✓ Tower Form Factor
- ✓ ECO Mode
- ✓ Overload Protection
- ✓ Smart Battery Management (SBM)



Aprašymas

CyberPower OLS3000EA-DE is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS is designed with color LCD panel for users to monitor power system and configure settings easily. This model is generator compatible and also adopts ECO mode to conserve power. The product can be connected to Emergency Power Off (EPO) switch, which allows users to shut off UPS immediately during emergency. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users.

Techninė specifikacija

Specifications	
Sandėlio grupė	Stromversorgung > USV [+474][-330]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	3 kVA
Output power	2700 W
Waveform	Pure sine
Input operation voltage (min)	190 V
Input operation voltage (max)	230 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	13.04 A
Surge energy rating	370 J
Response time	0 ms
Efficiency (ECO mode)	95%
Power factor	0.9
Input power factor	0.98
Crest factor	3:1
Output voltage Total Harmonic Distortion (THD)	5%
EMI/RFI noise filtering	Yes
Surge protection	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Battery replacement, Fault, Low battery alarm, Overload alarm
Ports & interfaces	
AC outlet types	C13 coupler
AC outlets quantity	7 AC outlet(s)
USB port	Yes
Battery	
Battery technology	Sealed Lead Acid (VRLA)
Number of batteries supported	3

Typical backup time at full load	4.2 min
Typical backup time at half load	13.1 min
Battery recharge time	4 h
Charging current	1.5 A

Design

Form factor	Tower
Product colour	Black
Housing material	Metal
Cable length	1.5 m
Built-in fan	Yes
Display type	LCD
LED indicators	Fault, Operation, Power, Status

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m

Certificates

Certification	RoHS, CE
---------------	----------

Packaging content

Cables included	Power load cable, USB cable
-----------------	-----------------------------

Weight & dimensions

Width	196 mm
Depth	416 mm
Height	337 mm
Weight	21.3 kg

Packaging data

Package width	295 mm
Package depth	519 mm
Package height	458 mm
Package weight	30.4 kg

Logistics data

Harmonized System (HS) code	8504408590
-----------------------------	------------

Country of origin	China
-------------------	-------

Matmenys ir svoris

Matmenys (I × P × A)	30,00cm × 52,00cm × 45,00cm
----------------------	-----------------------------