

Philips 4050 series 32BDL4050Q/00 Signage Display Digital signage flat panel 80 cm (31.5") 400 cd/m² Full HD Black Built-in processor Android 10

Gamintojas: **MMD - PHILIPS** · Modelis: **32BDL4050Q/00** · EAN: **8721038101706** · Prekės kodas: **515737**



584,90 €

Kaina su PVM

Be PVM: **483,39 €**

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Indoor Digital signage flat panel Black
- ✓ Ethernet LAN
- ✓ 80 cm (31.5") 1920 x 1080 pixels 400 cd/m²
- ✓ Built-in speaker(s) 10 W
- ✓ 60 Hz 8 ms

Aprašymas

Philips Signage 4050 Series

Efficiency made easy - your versatile 24/7 display

400 cd/m2 brightness

With 400 cd/m2 brightness for better visibility, the Philips Signage 4050 display is designed to be used 24/7, making it a great selection for travel and transportation hubs, retail centres, food and beverage locations, and more. FailOver is also included enabling your display to switch automatically between primary and secondary inputs should an outage occur.

Easily mounted in landscape or portrait.

Install in portrait or landscape orientations, with size variants to suit a range of installation purposes across the range of settings and industries.

Proven reliability. No need for external media player.

Tried, tested, and proven intuitive user experience, with a professional Android 10 SoC built in for easy apps and solutions integrations and no need for an external media player.

Remote management with Philips Wave

Manage your display and control content remotely with Philips Wave Controller – your evolutionary ecosystem designed to support time, energy and

cost efficiencies. Discover software applications to support your interactive vision from our network of proven partners on the PPDS ProStore.

Add optional Philips ScreenShare

Add in the fully secure and GDPR-compliant optional Philips ScreenShare presentation software for instant and effortless content sharing, using any device, on any network, and without additional hardware.

Supporting business sustainability and energy savings.

Supporting business sustainability and energy savings, with power saving features and using more environmentally friendly materials on the product and in the packaging.

Techninė specifikacija

Specifications	
Sandėlio grupė	Displays > Lcd Large Format [+94][-108]
Display	
Display diagonal	80 cm (31.5")
Display resolution	1920 x 1080 pixels
Display brightness	400 cd/m²
HD type	Full HD
Panel type	ADS
Native aspect ratio	16:9
Response time	8 ms
Contrast ratio (typical)	1200:1
Contrast ratio (dynamic)	500000:1
Viewing angle, horizontal	178°
Viewing angle, vertical	178°
Display number of colours	16.7 million colours
Pixel pitch	0.36375 x 0.36375 mm
Display diagonal (metric)	80 cm
Native refresh rate	60 Hz
Haze rate	25%
Ports & interfaces	
HDMI ports quantity	2
DVI port	Yes
USB port	Yes
HDMI version	2
DVI-I ports quantity	1
USB ports quantity	4

USB version	2.0/3.2 Gen 1 (3.1 Gen 1)
Ethernet LAN (RJ-45) ports	1
Audio (L/R) in	1
Audio (L/R) out	1
RS-232C	Yes
Card reader integrated	Yes
Compatible memory cards	MicroSD (TransFlash)
Audio	
Built-in speaker(s)	Yes
Number of built-in speakers	2
RMS rated power	10 W
Design	
Product design	Digital signage flat panel
Product colour	Black
Placement supported	Indoor
VESA mounting	Yes
Orientation	Horizontal/Vertical
Screen shape	Flat
Panel mounting interface	100 x 100,200 x 200 mm
Bezel width (bottom)	1.19 cm
Bezel width (side)	1.19 cm
Bezel width (top)	1.19 cm
Performance	
On Screen Display (OSD)	Yes
Mean time between failures (MTBF)	50000 h
Power	
Power consumption (typical)	26 W
Power consumption (standby)	0.5 W
Energy efficiency class (SDR)	G
AC input voltage	100 - 240 V
AC input frequency	50/60 Hz
Computer system	
Computer system	Yes
Built-in processor	Yes

Processor manufacturer	ARM
Processor family	ARM Cortex
Processor model	A55
Internal memory	3 GB
On-board graphics card model	ARM Mali-G52
Internal storage capacity	16 GB
Operating system installed	Android 10
Video formats supported	H.263, H.264, H.265, MPEG1, MPEG2, MPEG4, VP9
Audio formats supported	AAC, HE-AAC, MPEG
Image formats supported	BMP, JPEG, PNG, WEBP
Weight & dimensions	
Display width	726.5 mm
Display depth	65.1 mm
Display height	425.4 mm
Display weight	5.7 kg
Packaging content	
Remote control included	Yes
Batteries included	Yes
Cables included	Power, RS-232
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	20 - 80%
Storage temperature (T-T)	-20 - 60 °C
Storage relative humidity (H-H)	5 - 95%
Certificates	
Certification	CB, CE, FCC, Class A, VCCI, RoHS, UL
Network	
Ethernet LAN	Yes
Matmenys ir svoris	
Matmenys (I × P × A)	80,00cm × 51,00cm × 12,00cm
Svoris	7,58kg