

QNAP TVS-675 NAS Tower ZhaoXin KaiXian KX-6000 KX-U6580 8 GB DDR4 0 TB QuTS hero Black

Gamintojas: **QNAP** · Modelis: **TVS-675-8G** · EAN: **4713213519394** · Prekės kodas: **533377**



1 655,90 €

Kaina su PVM

Be PVM: **1 368,51 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Up to 5 Gbps transfer speeds can be achieved by setting port trunking with the two built-in 2.5GbE ports
- ✓ Install high-performance M.2 PCIe NVMe Gen 3 x1 SSDs or economical SATA 6Gb/s SSDs in the dedicated SSD slots for caching with improved random I/O or high-performance storage pools
- ✓ Two PCIe Gen 3 slots allow for installing 2.5/5/10GbE adapters, QM2 cards, or QXP storage expansion cards
- ✓ 4K media playback and real-time transcoding; directly output videos to an HDMI 2.0 display (up to 4K @60Hz)
- ✓ Supports storage for virtualization; hosts multiple virtual machines and containers to run a wide range of applications on one NAS device
- ✓ Flexibly scale the total storage capacity to match business growth by connecting QNAP expansion enclosures

Aprašymas

Cost-efficient 8-core 2.5GbE NAS, supporting M.2 SATA/NVMe SSD caching, PCIe expansion, and 4K HDMI display

Powered by the x86 architecture Zhaoxin KaiXian KX-U6580 8-core processor, the TVS-675 provides businesses with a modern 2.5GbE NAS solution to tackle everyday tasks like file backup/restore, and to boost team collaboration with higher productivity. Besides hardware advantages with built-in M.2 SSD slots for cache acceleration and PCIe expansion, the TVS-675 supports abundant business and media applications (including snapshot protection, virtual machines, cloud storage gateways, 4K HDMI display, and real-time transcoding) alongside expandable storage capacity and install-on-demand apps, making it a cost-effective and reliable data storage and media NAS.

High-performance multi-tasking with an 8 core 2.5GHz processor and up to 64 GB RAM

Powered by an x86 architecture Zhaoxin KaiXian KX-U6580 8 cores/8 threads 2.5GHz processor and 8 GB DDR4 memory (expandable up to 64 GB - 2x 32GB, dual channel support), the TVS-675 has enormous processing power to drive virtual machine performance and tackle complex multitasking workloads. AES-NI encryption support boosts encryption performance while also maintaining the security of your NAS data.

Streamline large file transfers and video editing with 2.5GbE

The TVS-675 comes with two 2.5GbE RJ45 (2.5G/1G/100M) LAN ports that allow you to use existing CAT5e cables to upgrade network speeds from 1 Gigabit to 2.5 Gigabit. The dual 2.5GbE ports also support Port Trunking for up to 5 Gbps transmission speeds, improving the business efficiency of bandwidth-hungry applications such as large file transfers, fast backup/restoration, and multimedia transfer & editing.

Future-proof your IT infrastructure for high-speed networks

The TVS-675 is also ideally matched with QNAP's managed and unmanaged 2.5GbE/10GbE switches to form high-speed, secure, and scalable network environments without going over budget. QNAP also provide 2.5GbE/5GbE/10GbE PCIe cards and USB 5GbE adapters for Windows®/Linux® workstations, allowing you to easily build a high-speed network environment for productive team collaboration.

Faster USB transfers

Featuring two USB 3.2 Gen 2 (10Gbps) and two USB 3.2 Gen 1 (5Gbps) ports, the TVS-675 allows compatibility with faster USB external drives/enclosures for transferring large media files. The TVS-675 also supports USB devices such as mobile phones and uninterruptible power supplies for greater all-round functionality.

Get performance benefits from SSD caching and Qtier Technology

To attain optimal I/O and reduce latency, you can configure SSD caching by using either 2.5-inch SSDs or the two built-in M.2 2280 SSDs slots (supports high-performance PCIe NVMe Gen 3 x1 SSDs or economical SATA 6Gb/s SSDs, sold separately) in the TVS-675. Extra M.2 SSD slots can also be added by installing QM2 PCIe cards, allowing you to configure your M.2 SSDs in a RAID 5/6 array to achieve higher sequential speed or a read-only cache speed similar to the performance of a RAID 10 array while maintaining high storage efficiency.

SSD Over-provisioning

You can add additional SSD over-provisioning to avoid write amplification and improve SSD random write speeds and endurance. You can potentially attain enterprise-grade SSD performance levels from affordable consumer SSDs!

SSD cache acceleration

Enable SSD caching for increasing IOPS performance and reducing latency for storage volume. This feature is perfect for IOPS-demanding applications including databases and virtualization.

Qtier for auto-tiering

Qtier technology drives auto-tiered storage with continuous data optimization across high-performance SSDs and high-capacity HDDs based on access frequency. I/O-Aware Qtier can reserve a cache-like space in the SSD tiered to handle burst I/O in real time.

Abundant I/O capabilities with PCIe expansion

The TVS-675 has two PCIe Gen 3 x4 slots that allow for installing various expansion cards for expanding application potential.

Direct 4K HDMI output for multimedia and virtual machine content

The TVS-675 features ZhaoXin® C-960 UHD Graphics that supports hardware decoding and real-time transcoding*. The HDMI 2.0 output supports up to 4K (3840 x 2160p) @60Hz, providing great benefits for applications like video production/editing or industrial design that demands high resolution and color realism as well as intensive media storage, transfer and display. By connecting the TVS-675 to an HDMI display, you can directly watch multimedia content saved on the NAS, or use the TVS-675 as a versatile workstation by directly outputting virtual machines from Virtualization Station or Linux Station.

Protect your data with higher security

The TVS-675 is loaded with comprehensive security features to keep your data safe.

- QuFirewall for network security: Supports IPv6, firewall access lists, and GeoIP filtering to restrict access upon the geographical location for higher network security.
- WPA2 Enterprise: Provides enterprise-grade wireless security for business networks, including certificate authority, encryption key, and enhanced encryption/decryption.
- Security Counselor: A security portal that checks for weaknesses and offers recommendations for enhancing NAS security. It also integrates anti-virus and anti-malware scanning software.

A secure file center supporting regular backups and snapshot protection

The TVS-675 provides a reliable, flexible backup and disaster recovery solution to simplify routine backup jobs cost-efficiently and with high productivity.

HBS simplifies 3-2-1 backup plans

HBS centralizes backup, restoration, and synchronization for easily backing up Windows® and Mac® data and transferring data in the TVS-675 to another QNAP NAS, remote server, or cloud storage space. HBS supports QuDedup technology that eliminates redundant data at the source and makes multi-version backup faster.

Snapshots multiply backup protection

Block-level snapshots are dependable data protection methods, especially in the face of growing ransomware threats. The TVS-675 supports up to 256 snapshots per volume/LUN, and up to 1,024 snapshots per NAS.

All-in-one virtual machine and container hosting solution

You can count on Virtualization Station and Container Station for comprehensive virtualization support. Coupled with the Network & Virtual Switch app that boosts interoperability between virtual machines, containers, QNAP NAS, and other networked devices, you can flexibly allocate physical and virtual network resources to simplify network deployment.

Virtualization Station

Run multiple Windows®, Linux®, UNIX®, Android™, and QuTScloud virtual machines and access them via a web browser or Virtual Network Computing (VNC). Businesses can run virtualized server applications on a single NAS without the need for additional physical servers.

Container Station

Experience LXC and Docker® lightweight virtualization technologies, download apps from the built-in Docker Hub Registry®, import and export containers, and create abundant microservices.

License-free VMware® and Hyper-V backup appliance

With Hyper Data Protector, the TVS-675 becomes an agentless backup tool for VMware® vSphere and Microsoft® Hyper-V VM backup. Hyper Data Protector features incremental backup, global deduplication, backup scheduling and recovery compression. Hyper Data Protector also simultaneously backs up multiple VMs, providing you with a cost-effective and reliable disaster recovery plan, ensuring 24/7 operation of your services.

Optimized collaboration with seamless file sharing and sync

The TVS-675 centrally stores data and files, and supports SMB/CIFS, AFP and NFS protocols for file sharing across Windows®, Mac®, and Linux®/UNIX® networks. Coupled with the Qsync utility, any file uploaded to the TVS-675 will become available for all linked devices (such as computers, laptops and mobiles). You can sync shared folders and team folders for group file sharing to enhance the flexibility of team projects and collaboration. The support of Azure Active Directory Domain Services (Azure AD DS), Windows AD® and LDAP services assist system administrators in managing user accounts and permissions for multiple NAS devices with greater efficiency.

Build an affordable Fibre Channel SAN environment

Common Fibre Channel Storage Area Networks (SAN) devices are often costly. By installing QNAP dual-port 16Gb Fibre Channel expansion cards in the TVS-675, you have more budget-friendly options to add a NAS to a SAN environment. You can set a Fibre Channel Target using the iSCSI & Fibre Channel app. Moreover, the LUN Masking and Port Binding features provide an additional layer of data security.

Subscribe to QVR Elite surveillance solution for 24/7 security

QVR Elite is QNAP's subscription-based smart surveillance solution, allowing you to easily build a surveillance system with lower TCO and higher scalability. You can arrange a dedicated, independent storage space for surveillance data on the TVS-675 and enjoy simplified camera management, storage space allocation, camera live viewing and playback. Recordings are saved as MP4 files, allowing playback on nearly every device. QVR Elite also integrates QNAP AI-based solutions to build smart facial recognition for retail and door access systems with QNAP NAS. With QVR Pro Client software installed on your Windows®/Mac® or mobile devices, taking full control over monitored areas becomes more convenient and easier.

More productivity applications

Linux Station

Run Linux® applications (including apps from the Linux Software Center) directly on the NAS and remotely access the Linux® desktop from a web browser.

Boxafe

Safeguard enterprise cloud data by backing up/syncing files, emails, calendars and contacts from Google™ Workspace and Microsoft® Office 365® to the TVS-675.

HybridMount

Integrate the NAS with mainstream cloud services. By deploying cloud storage gateways and enabling local caching on the TVS-675, you can seamlessly use the cloud for storage, backup, and data recovery with low-latency access.

QuObjects

A high-performance S3 compatible development environment on a NAS to simplify service development workflows from testing to production. You can also move cold data from the cloud to on-premises QuObjects for storage to save cloud storage costs.

QuMagie

An AI-powered photo management app, supporting automated photo categorization with AI Albums, iOS® Live Photo display, and powerful search tool. It supports Google Edge TPU to drive 10x faster image recognition!

Notification Center

Consolidates all system events, alerts, and notifications for smooth and easy NAS management, keeping you always informed of your NAS status.

Flexible and economical storage expansion

The storage capacity of the TVS-675 can be expanded using USB-based expansion enclosures (QXP USB storage expansion card required) or connecting SATA 6Gb/s JBOD units (QXP SATA storage expansion card required). NAS storage expansion management is made easy with the user-

friendly Storage & Snapshots Manager app.

Techninė specifikacija

Storage	
Storage drives installed	No
Total installed storage capacity	0 TB
Number of storage drives installed	0
Number of storage drives supported	6
Installed storage drive type	No
Supported storage drive types	HDD & SSD
Storage drive capacity	0 GB
RAID support	Yes
Supported storage drive interfaces	M.2, Serial ATA II, Serial ATA III
Storage drive sizes supported	2.5,3.5,M.2
Number of M.2 (M & B) slots	2
RAID levels	0, 1, 5, 6, 10, 50, 60, JBOD
Online RAID migration	Yes
Online RAID expansion	Yes
RAID rebuild	Yes
Hot-swap drive bays	Yes
Supported file systems	FAT32, HFS+, NTFS, exFAT, ext3, ext4
Bad block scan	Yes
Disk roaming	Yes
Processor	
Processor family	ZhaoXin KaiXian KX-6000
Processor manufacturer	ZhaoXin
Processor model	KX-U6580
Processor frequency	2.5 GHz
Processor cores	8
On-board graphics card model	ZhaoXin C960
Memory	
Internal memory	8 GB
Internal memory type	DDR4
Maximum RAM supported	64 GB
Memory slots	2

Memory form factor	SO-DIMM
Flash memory	5000 MB
Network	
Ethernet LAN	Yes
Ethernet LAN data rates	100,1000,2500 Mbit/s
DHCP client	Yes
DHCP server	Yes
Jumbo frames support	Yes
iSCSI support	Yes
Wake-on-LAN ready	Yes
Supported network protocols	IPv4, IPv6
Link aggregation	Yes
Load balancing system	Yes
Dynamic DNS (DDNS)	Yes
Ports & interfaces	
Ethernet LAN (RJ-45) ports	2
USB port	Yes
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	2
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2
HDMI ports quantity	1
HDMI version	2
Concurrent connections	2000
PCI Express x4 (Gen 3.x) slots	2
Design	
Chassis type	Tower
Cooling type	Active
Product colour	Black
Number of fans	3 fan(s)
Fan diameter	8 cm
LED indicators	HDD, LAN, SSD, Status, USB
Cable lock slot	Yes
Cable lock slot type	Kensington
Performance	
Type	NAS

Device class	Small & Medium Business
Backup function	Yes
Backup features	Cloud, USB drive, iSCSI LUN
Buzzer	Yes
Multilingual support	Yes
Number of users	2000 user(s)
Noise level	20.2 dB
Third-party support	Yes
Snapshot	Yes
Share folder access right management	Yes
Security algorithms	256-bit AES, FIPS 140-2, HTTPS, SNMPv2, SNMPv3, SSL/TLS
Access Control List (ACL)	Yes
Reset button	Yes
On/off switch	Yes
Built-in FTP server	Yes
Browser supported	Apple Safari, Google Chrome, Mozilla Firefox, Microsoft Edge
System log	Yes
Hot spare	Yes
Password authentication	Yes
Disk scan	Yes
S.M.A.R.T. support	Yes
Share folder	AFP, CIFS/SMB, FTP, WebDAV
USB copy function	Yes
Software	
Operating system installed	QuTS hero
Operating system version	h5.0.0
Windows operating systems supported	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 11, Windows 11 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64
Linux operating systems supported	CentOS 7.0, SuSE Linux 12.0, SuSE Linux 12.3, SuSE Linux 15, Ubuntu 14.04, Ubuntu 14.10, Ubuntu 15.04, Ubuntu 15.10, Ubuntu 16.04, Ubuntu 16.10, Ubuntu 17.10, Ubuntu 18.04 LTS, Ubuntu 20.04 LTS

Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur
Server operating systems supported	Windows Server 2003, Windows Server 2008 R2, Windows Server 2012, Windows Server 2012 R2, Windows Server 2016, Windows Server 2019
Other operating systems supported	IBM AIX 7.1, IBM AIX 7.2, Solaris 10, Solaris 11

Power

Power supply location	Built-in
Power supply unit (PSU) capacity	250 W
Number of power supply units	1
Power consumption (typical)	60.794 W
Power consumption (HDD standby)	41.897 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Fan voltage	12 V

Weight & dimensions

Width	263.9 mm
Depth	280.8 mm
Height	188.2 mm
Weight	6.2 kg
Package width	295 mm
Package depth	390 mm
Package height	417 mm
Package weight	7.85 kg

Packaging content

Cables included	AC, LAN (RJ-45)
Power cables quantity	1
Quick installation guide	Yes
Number of screws	36
Drive tray key included	Yes
Package type	Box

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	5 - 95%
Storage temperature (T-T)	-20 - 70 °C

Storage relative humidity (H-H)	5 - 95%
---------------------------------	---------

Logistics data

Harmonized System (HS) code	84714100
-----------------------------	----------

Other features

Fibre Channel	Yes
---------------	-----

Warranty period	3 year(s)
-----------------	-----------