



Akyga AK-B1-500E power supply unit 500 W 20+4 pin ATX ATX Grey

Modelis: AK-B1-500E

Gamintojas: AKYGA

EAN: 5901720133236

Prekės kodas: 538349

23.99€

Certification: CE, RoHS, REACH | Weight: 1.01 kg | Depth: 140 mm | Total power: 500 W | Package weight: 1.09 kg | Cables included: Peripheral (Molex) to SATA 3.3, SATA | EPS power connector (8-pin): No | Mean time between failures (MTBF): 100000 h | Peripheral (Molex) power connectors (4-pin): 2 | Manual: Yes | Package type: Box | Package height: 95 mm | Input current: 5 A | Package depth: 220 mm | On/off switch: Yes | Product colour: Grey | Power supply unit (PSU) form factor: ATX | Operating temperature (T-T): 5 - 50 °C | Package width: 160 mm | Max output current (+5V): 34 A | Number of SATA power connectors: 3 | Height: 85 mm | AC input voltage: 220 V | Width: 150 mm | Fan diameter: 12 cm | Combined power (+3.3V): 250 W | Power Factor Correction (PFC) type: Passive | Peripheral (Molex) power cable length: 300 | SATA power cable length: 300 mm | Number of fans: 1 fan(s) | Combined power (+5V): 250 W | Motherboard power connector: 20+4 pin ATX | ATX version: 2.31 | Purpose: PC | Combined power (+12V): 252 W | Warranty card: Yes | Max output current (+12V): 21 A | Max output current (+3.3V): 30 A | Number of cables: 4 | Voltage tolerance: 70% |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Supported motherboard form factors: ATX | Sustainability certificates: RoHS | ATX power connector (12+4 pin): Yes | Fan controller: Yes | Warnings: Avoid contact of the product with water or other liquids. | Warnings: Do not open the case - risk of electric shock. | Warnings: The product is not suitable for disposal with municipal waste - dispose of in accordance with local regulations.