



CyberPower CP900EPFCLCD uninterruptible power supply (UPS) Standby (Offline) 0.9 kVA 540 W 6 AC outlet(s)

Modelis: CP900EPFCLCD

Gamintojas: CYBERPOWER

EAN: 4712364142468

Prekės kodas: 538350

257.98€

Certification: CE, EAC, RCM | Compatible operating systems: Windows 7/Vista/XP/2000/Server 2003, Linux | Output power capacity: 0.9 kVA | UPS topology: Standby (Offline) | Storage relative humidity (H-H): 0 - 95% | Output power: 540 W | Auto-restart: Yes | Storage temperature (T-T): 15 - 45 °C | Housing material: Plastic | AC outlet types: Type F | Depth: 230 mm | Operating temperature (T-T): 0 - 40 °C | Surge protection features: Network | Surge protection features: Telephone | Package width: 195 mm | Surge protection features: Modem | Number of batteries supported: 1 | Package height: 335 mm | Typical backup time at full load: 1 min | Output voltage Total Harmonic Distortion (THD):

10% | EMI/RFI noise filtering: Yes | Power protection features: Short circuit | Power protection

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

features: Over voltage | Display type: LCD | Operating temperature (T-T): 32 - 104 °F | Power plug: C14 coupler | Nominal input voltage: 165-265 V | Audible alarm(s): Yes | Interface: USB | Audible alarm modes: Alarm when on battery, Low battery alarm, Overload alarm | Surge protection: Yes | Waveform: Pure sine | Form factor: Tower | Input operation voltage (min): 170 V | Input frequency: 50/60 Hz | Typical backup time at half load: 7 min | Operating relative humidity (H-H): 0 - 95% | Nominal output voltage: 230 V | Non-operating altitude: 0 - 15000 m | Harmonized System (HS) code: 8504408590 | Surge protection features: Fax | Battery recharge time: 8 h | Output frequency: 50/60 Hz | Power protection features: Over power | Power protection features: Overload | Height: 275 mm | Input operation voltage (max): 270 V | Maximum current: 10 A | Surge energy rating: 405 J | Modem (RJ-11) ports: 1 | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Cable length: 1.83 m | Product colour: Black | USB 2.0 ports quantity: 1 | Response time: 4 ms | AC outlets quantity: 6 AC outlet(s) | Ethernet LAN (RJ-45) ports: 1 | Battery voltage: 230 V | Operating altitude: 0 - 3000 m | Weight: 6.6 kg | LED indicators: Operation | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating.