



CyberPower PR1000ELCD uninterruptible power supply (UPS) Line- Interactive 1 kVA 900 W 8 AC outlet(s)

Modelis: PR1000ELCD

Gamintojas: CYBERPOWER

EAN: 4712364143809

Prekės kodas: 538351

530.98€

Certification: CE, EAC, RCM, RoHS | Compatible operating systems: Windows 7 / Vista / XP / 2000, Server 2003 / 2008, Linux | Output frequency: 50/60 Hz | Surge energy rating: 405 J | Hot-swap battery: Yes | UPS topology: Line-Interactive | AC outlet types: C13 coupler | Automatic Voltage Regulation (AVR): Yes | Number of output IEC jumpers: 1 | Harmonized System (HS) code: 8504408590 | Waveform: Pure sine | Battery technology: Sealed Lead Acid (VRLA) | AC outlets quantity: 8 AC outlet(s) | Operating temperature (T-T): 0 - 40 °C | Typical backup time at full load: 4 min | Width: 170 mm | Weight: 18.9 kg | Surge protection: Yes | Typical backup time at half load: 16 min | Power protection features: Overload | Display type: LCD | Non-operating altitude: 0 - 15000 m |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Output power capacity: 1 kVA | Depth: 432 mm | Response time: 4 ms | Overload protection: Yes | EMI/RFI noise filtering: Yes | Cables included: USB cable | Height: 221 mm | Input frequency: 50/60 Hz | Output power: 900 W | Serial ports quantity: 1 | Product colour: Black | LED indicators: Operation | LED indicators: Error | Operating relative humidity (H-H): 0 - 95% | Storage temperature (T-T): -15 - 45 °C | Operating altitude: 0 - 3000 m | USB 2.0 ports quantity: 1 | Input operation voltage (max): 301 V | Input operation voltage (min): 151 V | Output operation voltage (min): 230 V | Power plug: C14 coupler | Package height: 360 mm | Storage relative humidity (H-H): 0 - 95% | Output operation voltage (max): 230 V | Number of batteries supported: 1 | Housing material: Metal | Power factor: 0.9 | Battery recharge time: 8 h | Form factor: Tower | Package width: 316 mm | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating.