



Ever SINLINE RT 3000 Line- Interactive 3 kVA 2250 W 8 AC outlet(s)

Modelis: W/SRTLRT-003K00/00

Gamintojas: EVER

EAN: 5907683603748

Prekės kodas: 538356

1,045.98€

Width: 440 mm | Manual: Yes | Output operation voltage (max): 253 V | Display type: LCD | Number of batteries supported: 4 | Package height: 247 mm | Cables included: Input power cable | Input operation voltage (min): 178 V | Input operation voltage (max): 281 V | Height: 132 mm | Power plug: C20 coupler | Input frequency: 50 Hz | Typical backup time at half load: 7 min | Cold start: Yes | Waveform: Sine | Number of phases: 1 | Typical backup time at full load: 3 min | Power protection features: Overload | Surge protection: Yes | International Protection (IP) code: IP20 | Maximum current: 16 A | Power protection features: Short circuit | Battery recharge time: 4 h | Automatic Voltage Regulation (AVR): Yes | Output operation voltage (min): 195 V | Number of input phases: 1 | Number of output phases: 1 | Quick installation guide: Yes | Output power: 2250 W | Emergency Power Off (EPO): Yes | Rubber feet: Yes | Output power capacity: 3 kVA | UPS topology: Line-Interactive | Depth: 460 mm | AC outlet types: C13 coupler | Storage temperature (T-T): 0 - 45 °C | Operating altitude: 0 - 1000 m | Battery capacity: 9 Ah | Operating relative humidity (H-H): 20 - 80%

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| Cooling type: Active | LED indicators: Yes | Weight: 28 kg | Form factor: Rackmount/Tower |
Package width: 547 mm | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 |
Storage relative humidity (H-H): 20 - 95% | USB 2.0 ports quantity: 1 | AC outlets quantity: 8 AC
outlet(s) | Battery voltage: 12 V | Product colour: Black