



ASUS Prime AP-750G power supply unit 750 W 20+4 pin ATX ATX Black, White



Modelis: 90YE00U1-B0NA00

Gamintojas: ASUS

EAN: 4711387192962

Prekės kodas: 538392

84.99€

Cooling type: Active | On/off switch: Yes | Package depth: 208 mm | AC input voltage: 100 - 240 V | Product colour: White | Package width: 346 mm | Weight: 1.47 kg | Product colour: Black | Package weight: 2.88 kg | Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA | Depth: 150 mm | Peripheral (Molex) power connectors (4-pin): 3 | Width: 150 mm | Package height: 144 mm | Package type: Box | SATA power cable length: 400 | Purpose: PC | SATA power cable length: 120 | Bearing technology: Ball bearing | CPU P4 connector (4-pin): 2 | Power protection features: Over power | PCI Express power connectors (16-pin): 1 | Power protection features: Under voltage | Combined power (+5V): 110 W | Power protection features: Overheating | Max output current (-12V): 0.3 A | Power protection features: Short circuit | Power protection features: Over voltage | Total power: 750 W | Combined power (+5Vsb): 12.5 W | Combined power (+3.3V): 110 W | Cabling type: Fully-Modular | Efficiency: 92% | Motherboard power cable length: 61 cm | Peripheral (Molex) power cable length:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

400 | Combined power (-12V): 3.6 W | Height: 86 mm | Peripheral (Molex) power cable length: 150 mm | Power protection features: Overcharge | Max output current (+12V): 62 A | Max output current (+5Vsb): 2.5 A | Max output current (+3.3V): 20 A | Power supply unit (PSU) form factor: ATX | Power Factor Correction (PFC) type: Active | Number of SATA power connectors: 5 | ATX power connector (20+4 pin): Yes | PCI Express power connectors (8-pin): 3 | Motherboard power connector: 20+4 pin ATX | ATX version: 3.0 | CPU power connector (4+4 pin): Yes | 80 PLUS certification: 80 PLUS Gold | Max output current (+5V): 20 A | Combined power (+12V): 744 W | Mean time between failures (MTBF): 120000 h | CPU power cable length: 65 cm