



CyberPower BR1200ELCD uninterruptible power supply (UPS) Line- Interactive 1.2 kVA 720 W 8 AC outlet(s)

Modelis: BR1200ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856271232

Prekės kodas: 538479

222.99€

Ethernet LAN (RJ-45) ports: 2 | Battery voltage: 230 V | Operating temperature (T-T): 0 - 40 °C |
Weight: 8.2 kg | Output power: 720 W | Surge protection features: Network | Surge protection
features: Telephone | Width: 166 mm | UPS topology: Line-Interactive | Package height: 230 mm |
Storage temperature (T-T): -20 - 50 °C | Form factor: Desktop | Response time: 4 ms | Number of
batteries supported: 2 | Harmonized System (HS) code: 8504408590 | Output power capacity: 1.2
kVA | Package width: 158 mm | Surge protection features: Modem | Typical backup time at full load:
2 min | Depth: 288 mm | Replacement battery cartridge: RBP0063 | Modem (RJ-11) ports: 2 | AC
outlet types: Type F | Surge protection: Yes | Automatic Voltage Regulation (AVR): Yes | Typical

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

backup time at half load: 9 min | LED indicators: Power | USB 2.0 ports quantity: 1 | Sustainability compliance: Yes | Storage relative humidity (H-H): 0 - 90% | Input operation voltage (min): 165 V | Display type: LCD | Output frequency: 50/60 Hz | Waveform: Sine | USB port: Yes | Power protection features: Short circuit | LED indicators: Battery level | Heat dissipation: 137 BTU/h | Operating altitude: 0 - 3000 m | Cable length: 1.5 m | Product colour: Black | Input operation voltage (max): 290 V | Surge protection features: Fax | Operating relative humidity (H-H): 0 - 90% | AC outlets quantity: 8 AC outlet(s) | Housing material: Plastic | LED indicators: Status | Battery technology: Sealed Lead Acid (VRLA) | Height: 118 mm | EMI/RFI noise filtering: Yes | Audible alarm(s): Yes | USB port type: USB Type-A | Input frequency: 50/60 Hz | Number of phases: 1 | Output operation voltage (min): 220 V | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Surge energy rating: 150 J | Battery recharge time: 8 h | Non-operating altitude: 0 - 3000 m | Output operation voltage (max): 240 V | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: EAC