



CyberPower UT850EG-FR uninterruptible power supply (UPS) Line- Interactive 0.85 kVA 425 W 3 AC outlet(s)

Modelis: UT850EG-FR

Gamintojas: CYBERPOWER

EAN: 4712856273311

Prekės kodas: 538480

103.99€

Certification: CE | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Compliance certificates: RoHS | Product colour: Black | Input operation voltage (max): 290 V | Operating altitude: 0 - 3000 m | LED indicators: Yes | Cable length: 1.2 m | Response time: 4 ms | Non-operating altitude: 0 - 3000 m | Output operation voltage (max): 230 V | AC outlets quantity: 3 AC outlet(s) | Weight: 4.2 kg | EMI/RFI noise filtering: Yes | Operating temperature (T-T): 0 - 40 °C | Output power capacity: 0.85 kVA | AC outlet types: Type E | Battery recharge time: 6 h | Depth: 280 mm | Input frequency: 50/60 Hz | Automatic Voltage

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Regulation (AVR): Yes | UPS topology: Line-Interactive | Operating relative humidity (H-H): 0 - 90% | Height: 174 mm | Power protection features: Overload | Audible alarm(s): Yes | Battery technology: Sealed Lead Acid (VRLA) | Input operation voltage (min): 165 V | Output power: 425 W | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Storage temperature (T-T): -20 - 50 °C | Width: 84 mm | USB port: Yes | Form factor: Tower | Waveform: Sine | Storage relative humidity (H-H): 0 - 90% | Housing material: Plastic