



CyberPower Tracer III VP700ELCD-FR uninterruptible power supply (UPS) Line- Interactive 0.7 kVA 390 W 4 AC outlet(s)

Modelis: VP700ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856274851

Prekės kodas: 538482

142.99€

Certification: CE, RCM | Serial interface: Yes | USB port type: USB Type-B | Compliance certificates: RoHS | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Storage relative humidity (H-H): 0 - 90% | Housing material: Plastic | AC outlets quantity: 4 AC outlet(s) | Input frequency: 50/60 Hz | Noise level: 40 dB | Surge energy rating: 450 J | Battery recharge time: 8 h | Cable length: 1.5 m | Output operation voltage (max): 230

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

V | Typical backup time at full load: 1 min | Cables included: USB cable | Non-operating altitude: 0 - 3048 m | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Form factor: Tower | Waveform: Sine | Operating temperature (T-T): 0 - 40 °C | Maximum current: 3.04 A | Response time: 4 ms | Typical backup time at half load: 10 min | Product colour: Black | Height: 2227 mm | Manual: Yes | LED indicators: Yes | Depth: 260 mm | Output power capacity: 0.7 kVA | UPS topology: Line-Interactive | Surge protection: Yes | Operating relative humidity (H-H): 0 - 90% | Display type: LCD | Input operation voltage (max): 295 V | AC outlet types: Type E | USB 2.0 ports quantity: 1 | Operating altitude: 0 - 3048 m | Output power: 390 W | Storage temperature (T-T): -20 - 50 °C | Ethernet LAN (RJ-45) ports: 1 | Weight: 5.14 kg | Audible alarm(s): Yes | EMI/RFI noise filtering: Yes | Serial interface type: RS-232 | Automatic Voltage Regulation (AVR): Yes | Input operation voltage (min): 167 V | Serial ports quantity: 1 | Output frequency: 50/60 Hz | USB port: Yes | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm