



CyberPower Tracer III VP1000ELCD-FR uninterruptible power supply (UPS) Line- Interactive 1 kVA 550 W 4 AC outlet(s)

Modelis: VP1000ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856274868

Prekės kodas: 538483

155.99€

Certification: CE, RCM | Output power capacity: 1 kVA | Serial interface: Yes | Non-operating altitude: 0 - 3048 m | Waveform: Sine | Input operation voltage (max): 295 V | Input operation voltage (min): 167 V | Automatic Voltage Regulation (AVR): Yes | Maximum current: 4.35 A | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | UPS topology: Line-Interactive | Surge energy rating: 450 J | AC outlet types: Type E | Input frequency: 50/60 Hz | Output frequency: 50/60 Hz | Output operation voltage (max): 230 V | Surge protection: Yes | Serial interface type: RS-

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

232 | Display type: LCD | EMI/RFI noise filtering: Yes | USB port type: USB Type-B | Compliance certificates: RoHS | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Storage temperature (T-T): -20 - 50 °C | Cable length: 1.5 m | Operating temperature (T-T): 0 - 40 °C | Weight: 6.23 kg | Ethernet LAN (RJ-45) ports: 1 | Output power: 550 W | Product colour: Black | Depth: 260 mm | Audible alarm(s): Yes | Manual: Yes | Response time: 4 ms | Operating relative humidity (H-H): 0 - 90% | Cables included: USB cable | Height: 227 mm | Typical backup time at half load: 9 min | USB 2.0 ports quantity: 1 | AC outlets quantity: 4 AC outlet(s) | Battery recharge time: 8 h | Operating altitude: 0 - 3048 m | LED indicators: Yes | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Serial ports quantity: 1 | Noise level: 40 dB | Typical backup time at full load: 1 min | USB port: Yes | Form factor: Tower | Storage relative humidity (H-H): 0 - 90% | Housing material: Plastic