



CyberPower CP1350EPFCLCD uninterruptible power supply (UPS) Line- Interactive 1.35 kVA 780 W 6 AC outlet(s)

Modelis: CP1350EPFCLCD

Gamintojas: CYBERPOWER

EAN: 4711027798578

Prekės kodas: 538488

345.00€

Form factor: Tower | Weight: 10.9 kg | Product colour: Black | Output power: 780 W | Cooling type: Passive | Noise level: 35 dB | Battery capacity: 8.5 Ah | USB 2.0 ports quantity: 3 | AC outlets quantity: 6 AC outlet(s) | LED indicators: Yes | Battery voltage: 12 V | Width: 100 mm | Number of batteries supported: 2 | Ethernet LAN (RJ-45) ports: 1 | Surge protection features: Digital Subscriber Line (DSL) | Serial ports quantity: 1 | Output frequency: 50/60 Hz | Input frequency: 50/60 Hz | Surge protection features: Network | Surge protection features: Telephone | Serial interface: Yes | Auto-restart: Yes | Typical backup time at full load: 4 min | Surge protection features: Modem | Display type: LCD | Number of type F outputs: 6 | EMI/RFI noise filtering: Yes | Typical backup time at half

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

load: 10 min | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Depth: 370 mm | Output power capacity: 1.35 kVA | UPS topology: Line-Interactive | USB port: Yes | Automatic Voltage Regulation (AVR): Yes | Input operation voltage (max): 265 V | Surge protection: Yes | Modem (RJ-11) ports: 1 | Power protection features: Overload | Cabling technology: 10/100/1000Base-T(X) | Height: 265 mm | Sustainability certificates: RoHS | Audible alarm(s): Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Waveform: Sine | Surge protection features: Fax | Efficiency: 98.5% | Power plug: C14 coupler | Input operation voltage (min): 165 V | Nominal output voltage: 230 V | Battery recharge time: 8 h