



CyberPower CP1600EPFCLCD uninterruptible power supply (UPS) Line- Interactive 1.6 kVA 1000 W 6 AC outlet(s)

Modelis: CP1600EPFCLCD

Gamintojas: CYBERPOWER

EAN: 4711027798615

Prekės kodas: 538489

427.99€

Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Operating temperature (T-T): 0 - 40 °C | Storage temperature (T-T): -15 - 45 °C | Typical backup time at full load: 2.6 min | Weight: 11 kg | AC outlet types: Type F | Depth: 355 mm | Output power capacity: 1.6 kVA | Output power: 1000 W | Cable length: 1.83 m | Waveform: Pure sine | AC outlets quantity: 6 AC outlet(s) | Ethernet LAN (RJ-45) ports: 2 | Input frequency: 50/60 Hz | Replacement battery cartridge: RBP0142 | UPS topology: Line-Interactive | Display type: LCD |

Storage relative humidity (H-H): 0 - 95% | Form factor: Tower | Operating relative humidity (H-H): 0 -

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

95% | Surge energy rating: 405 J | Product colour: Black | Package width: 195 mm | USB port type: USB Type A/USB Type-C | USB port: Yes | Detachable power cord: Yes | Typical backup time at half load: 9.7 min | Harmonized System (HS) code: 8504408590 | Battery technology: Sealed Lead Acid (VRLA) | Width: 100 mm | Package height: 370 mm | Input operation voltage (max): 240 V | LED indicators: Power | Input operation voltage (min): 220 V | Height: 280 mm | Battery recharge time: 8 h | Power source type: AC | Sustainability certificates: RoHS | Sustainability compliance: Yes | Sustainability certificates: CE