

CyberPower OLS1000EA uninterruptible power supply (UPS) Double-conversion (Online) 1 kVA 900 W 3 AC outlet(s)

Gamintojas: **CYBERPOWER** · Modelis: **OLS1000EA-DE** · EAN: **4711027790190** · Prekės kodas: **538492**



275,90 €

Kaina su PVM

Be PVM: 228,02 €

Sandėlyje



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ Online (Double Conversion) UPS Topology
- ✓ Generator Compatible
- ✓ Zero Transfer Time
- ✓ Surge and Spike Protection
- ✓ Variable Speed Fans
- ✓ Emergency Power Off (EPO) Port
- ✓ SNMP/HTTP Remote Management Capability (Optional)
- ✓ ECO Mode
- ✓ Overload Protection



Aprašymas

CyberPower OLS1000EA is a high-performance UPS featuring online double-conversion topology, which provides seamless Pure Sine Wave power for mission-critical devices such as NAS and servers, DVRs/surveillance systems, transportation and infrastructure, and emergency systems. It's typically integrated in the back office, server room, and data center environment.

The UPS is designed with color LCD panel for users to monitor power system and configure settings easily. This model is generator compatible and also adopts ECO mode to conserve power. The product can be connected to Emergency Power Off (EPO) switch, which allows users to shut off UPS immediately during emergency. The variable speed fans provide automatic thermal management based on power load to reduce noise and provide greater comfort for users

Techninė specifikacija

Specifications	
Sandėlio grupė	UPS power supplies [+77][-127]
Features	
UPS topology	Double-conversion (Online)
Output power capacity	1 kVA
Output power	900 W
Waveform	Pure sine
Input operation voltage (min)	160 V
Input operation voltage (max)	300 V
Input frequency	50/60 Hz
Output operation voltage (min)	208 V
Output operation voltage (max)	240 V
Output frequency	50/60 Hz
Maximum current	4.5 A
Surge energy rating	345 J
Response time	0 ms
Efficiency (ECO mode)	95%
Input power factor	0.98
Output power factor	0.9
Crest factor	3:1
ECO mode	Yes
Emergency Power Off (EPO)	Yes
Output voltage Total Harmonic Distortion (THD)	3%
EMI/RFI noise filtering	Yes
Power protection features	Overload
Audible alarm(s)	Yes
Audible alarm modes	Battery replacement, Fault, Overload alarm
Ports & interfaces	
AC outlet types	IEC 320
Power plug	C13 coupler
AC outlets quantity	3 AC outlet(s)
USB port	Yes
Battery	

Battery technology	Sealed Lead Acid (VRLA)
Typical backup time at full load	4 min
Typical backup time at half load	11 min
Battery life (max)	4 year(s)
Charging current	1.5 A
Design	
Form factor	Tower
Product colour	Black
Housing material	Metal
Cable length	1.5 m
Built-in fan	Yes
Display type	LCD
Operational conditions	
Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 50 °C
Operating relative humidity (H-H)	20 - 90%
Storage relative humidity (H-H)	10 - 90%
Operating altitude	0 - 1500 m
Non-operating altitude	0 - 1500 m
Certificates	
Compliance certificates	CE, RoHS
Packaging content	
Cables included	USB cable
Manual	Yes
Weight & dimensions	
Width	140 mm
Depth	327 mm
Height	191 mm
Weight	9.4 kg
Packaging data	
Package width	241 mm
Package depth	510 mm
Package height	313 mm
Package weight	14.6 kg

Logistics data	
Harmonized System (HS) code	8504408590
Country of origin	China
Matmenys ir svoris	
Matmenys (l × p × a)	28,00cm × 43,00cm × 21,00cm
Svoris	10,00kg