



Eaton 5PX Gen2 uninterruptible power supply (UPS) Line- Interactive 3 kVA 3000 W 10 AC outlet(s)

Modelis: 5PX3000IRTNG2

Gamintojas: EATON

EAN: 743172104656

Prekės kodas: 538505

2,631.99€

Certification: IEC/EN 62040-2, FCC B, CISPR22 B CB (TUV) / cTUVus / EAC / UKCA / Ukr / Cm | Output connections: 8 x IEC C13 (10A) 2 x IEC C19 (16A) | Product colour: Black | Display type: LCD | Nominal output voltage: 230 V | Automatic battery test: Yes | Management card included: Yes | Noise level: 40 dB | Form factor: Rackmount/Tower | Safety: IEC/EN 62040-1, UL1778, CSA22.2 | Input frequency: 47/70 Hz | Serial interface: Yes | Power protection features: Overdischarge | Output power: 3000 W | Waveform: Pure sine | Width: 438 mm | LED indicators: Yes | Harmonized System (HS) code: 85078000 | Input operation voltage (min): 160 V | Power plug: C20 coupler | Hot-swap battery: Yes | Cabling technology: 10/100/1000Base-T(X) | Height: 85.5 mm | Serial interface type: RS-232 | Depth: 483 mm | AC outlet types: C19 coupler | Input operation voltage (max): 294 V | USB

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

port: Yes | UPS topology: Line-Interactive | Serial ports quantity: 1 | AC outlet types: C13 coupler | Rack capacity: 2U | Output power capacity: 3 kVA | Operating temperature (T-T): 0 - 40 °C | Weight: 31.7 kg | AC outlets quantity: 10 AC outlet(s) | Compliance certificates: CE | Sustainability certificates: ENERGY STAR | Sustainability compliance: Yes