



Gembird EG-UPS-035 uninterruptible power supply (UPS) Line- Interactive 2 kVA 1200 W 5 AC outlet(s)

Modelis: EG-UPS-035

Gamintojas: ENERGENIE

EAN: 8716309116602

Prekės kodas: 538507

174.99€

Waveform: Sine/Square | Package width: 300 mm | Operating temperature (T-T): 0 - 40 °C | Battery voltage: 12 V | USB port type: USB Type-B | Ethernet LAN (RJ-45) ports: 1 | Input frequency: 50/60 Hz | Package type: Box | Package height: 180 mm | Input operation voltage (max): 295 V | Product colour: Black | Output frequency: 50/60 Hz | Operating relative humidity (H-H): 20 - 90% | Weight: 12.9 kg | Surge protection: Yes | UPS topology: Line-Interactive | Depth: 400 mm | Number of batteries supported: 2 | Battery capacity: 9 Ah | LED indicators: Yes | Input operation voltage (min): 162 V | Power protection features: Overdischarge | USB port: Yes | Height: 125 mm | Power protection features: Overcharge | Power protection features: Short circuit | Noise level: 45 dB |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Output power capacity: 2 kVA | AC outlet types: C13 coupler | Cold start: Yes | Cables included: Input power cable, USB cable | Display type: LCD | Response time: 10 ms | Form factor: Tower | Width: 220 mm | Typical backup time at half load: 8 min | Typical backup time at full load: 20 min | Power plug: C14 coupler | Battery technology: Sealed Lead Acid (VRLA) | AC outlets quantity: 5 AC outlet(s) | Automatic Voltage Regulation (AVR): Yes | Charging current: 0.5 A | Output power: 1200 W | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Keep away from sources of fire and water. | Customs product code (TARIC): 8504408590 | Compliance certificates: RoHS | Compliance certificates: CE | Output operation voltage (max): 220 V | Battery recharge time: 8 h | Sustainability compliance: Yes