



TP-Link Omada ES208G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black



Modelis: ES208G

Gamintojas: TP-LINK

EAN: 1210002600668

Prekės kodas: 538631

39.99€

Width: 158 mm | MAC address table: 8000 entries | Auto-negotiation: Yes | Rack mounting: No | IGMP snooping: Yes | Operating temperature (T-T): -5 - 45 °C | Mean time between failures (MTBF): 1141726 h | Input current: 0.6 A | Loop protection: Yes | LED indicators: Yes | Power over Ethernet (PoE): No | Port mirroring: Yes | Cloud-managed: Yes | Power supply included: Yes | Surge protection voltage: 6 kV | Height: 25.4 mm | Wall mountable: Yes | Operating relative humidity (H-H): 10 - 90% | Fanless: Yes | DHCP features: DHCP client | Power source: DC | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Heat dissipation: 9.09 BTU/h | Switch type: Managed | DC input voltage: 5 V | Firmware upgradeable: Yes | Switch layer: L2 | Stackable: No | Virtual LAN features: Tagged VLAN | Virtual LAN features: MTU VLAN | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

consumption (max): 2.7 W | Switching capacity: 16 Gbit/s | Package type: Box | VLAN support: Yes | Number of VLANs: 32 | User guide: Yes | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Flash memory: 64 MB | Basic switching RJ-45 Ethernet ports quantity: 8 | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | AC adapter included: Yes | Networking standards: IEEE 802.1ab | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Web-based management: Yes | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3i | Surge protection: Yes | Jumbo frames support: Yes | Jumbo frames: 15000 | Link aggregation: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Gigabit Ethernet (copper) ports quantity: 8 | Store-and-forward: Yes | Networking standards: IEEE 802.3at | Forwarding rate: 11.9 Mpps | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Fast leave: Yes | Zero Touch Provisioning (ZTP): Yes | Unified static configuration: Yes