



**TP-Link Omada
ES228GMP
network switch
Managed L2
Gigabit Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Black**

Modelis: ES228GMP

Gamintojas: TP-LINK

EAN: 1210002600989

Prekės kodas: 538632

306.99€

Certification: FCC, CE, RoHS | Fast leave: Yes | Unified static configuration: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Ethernet LAN data rates: 10,100,1000 Mbit/s | AC input frequency: 50/60 Hz | Product colour: Black | Networking standards: IEEE 802.3af | Web-based management: Yes | Networking standards: IEEE 802.3u | Firmware upgradeable: Yes | Operating temperature (T-T): -5 - 45 °C | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3z | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power consumption (max): 454.8 W | Quick start guide: Yes | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1ab | Storage relative humidity (H-H): 5 - 90% | LED indicators: Yes | Networking standards: IEEE 802.3i | Noise level: 46.2 dB | Power over Ethernet (PoE): Yes | AC input voltage: 100 - 240 V | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Height: 44 mm | Power source: AC | Total Power over Ethernet (PoE) budget: 384 W | Cables included: AC | Number of fans: 2 fan(s) | Copper ethernet cabling technology: 1000BASE-X | VLAN support: Yes | Surge protection: Yes | Flash memory: 64 MB | Copper ethernet cabling technology: 1000BASE-T | Width: 440 mm | Rack mounting: Yes | Auto MDI/MDI-X: Yes | Depth: 330 mm | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-X | Manual: Yes | Power over Ethernet (PoE) power per port: 30 W | Housing material: Metal | Number of VLANs: 32 | 10G support: No | Store-and-forward: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Jumbo frames support: Yes | Fanless: No | Broadcast storm control: Yes | Gigabit Ethernet (copper) ports quantity: 26 | Power over Ethernet (PoE) type supported: PoE+ | Heat dissipation: 1546.15 BTU/h | Link aggregation: Yes | DHCP features: DHCP client | Virtual LAN features: Port-based VLAN | Surge protection voltage: 6 kV | Switch layer: L2 | SFP module slots quantity: 2 | Virtual LAN features: Tagged VLAN | Virtual LAN features: MTU VLAN | Switching capacity: 56 Gbit/s | Multicast support: Yes | Jumbo frames: 15000 | Power supply included: Yes | Mean time between failures (MTBF): 224143 h | Switch type: Managed | IGMP snooping: Yes | MAC address table: 8000 entries | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | Rack mount kit: Yes | Cloud-managed: Yes | Packet buffer memory: 4 MB | Port mirroring: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000)