



Digitus 1D Barcode Hand Scanner



Modelis: DA-81001

Gamintojas: DIGITUS

EAN: 4016032473633

Prekės kodas: 538695

20.99€

Compatible operating systems: Mac/Linux | Warnings: Avoid direct contact with eyes. | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | International Protection (IP) code: IP54 | Operating temperature (T-T): -20 - 50 °C | Maximum scan width: 30 cm | Product colour: Black | Height: 165 mm | Country of origin: China | Depth: 87 mm | Scanner type: 1D | Sensor type: Linear | Standard interfaces: RJ-45, USB | Light source: 650 nm | Power source type: USB | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Industrial 2 of 5 | Windows operating systems supported: Yes | Tilt reading angle: -45 - 45° | Connectivity technology: Wired | Linear (1D) barcodes supported: Code 128 | Linear (1D) barcodes supported: EAN 128 | Width: 63 mm | Linear (1D) barcodes supported: GS1-128 (UCC/EAN-128) | Linear (1D) barcodes supported: Code 39 | Input voltage: 5 V | Weight: 110 g | Linear (1D) barcodes supported: EAN-13 | Linear (1D) barcodes supported: EAN-8 | Harmonized System (HS) code: 84716070 | Housing material: Acrylonitrile butadiene styrene (ABS) | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: ITF-6 | Linear (1D) barcodes supported: Codabar | Linear (1D) barcodes supported: ITF-14 | Linear (1D) barcodes supported: ISSN | Linear (1D)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

barcodes supported: Code 32 | Housing material: Polycarbonate (PC) | Type: Handheld bar code reader | 2D (matrix & stacked) barcodes supported: Not supported | Storage temperature (T-T): -40 - 70 °C | Power consumption: 100 mA | Linear (1D) barcodes supported: GS1 DataBar | Linear (1D) barcodes supported: IATA | Cable length: 2 m | Mobile operating systems supported: Android | Mobile operating systems supported: iOS