



TP-Link Omada 28-Port Gigabit Smart Switch with 16-Port PoE+



Modelis: SG2428LP

Gamintojas: TP-LINK

EAN: 8885020620832

Prekės kodas: 538720

286.00€

Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 150 W | Web-based management: Yes | MAC address filtering: Yes | AC input frequency: 50/60 Hz | SFP module slots quantity: 4 | Power source: AC/PoE | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3at | Virtual LAN features: Voice VLAN | Width: 440 mm | Virtual LAN features: Tagged VLAN | Multicast support: Yes | 10G support: No | DHCP features: DHCP relay | Rack mounting: Yes | IGMP snooping: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switching capacity: 56 Gbit/s | Depth: 220 mm | Number of VLANs: 4000 | Power over Ethernet plus (PoE+) ports quantity: 16 | Forwarding rate: 41.66 Mpps | Virtual LAN features: Protocol-based VLAN | Virtual LAN features: MAC address-based VLAN | DHCP features: DHCP server | Height: 44 mm | Product colour: Grey | Power consumption (max): 184.7 W | Power over Ethernet (PoE): Yes | LED indicators: Yes | Heat dissipation: 628 BTU/h | Access Control List (ACL): Yes | Switch layer: L2/L2+ |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

MAC address table: 8000 entries | AC input voltage: 100 - 240 V | Auto-negotiation: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Storage relative humidity (H-H): 5 - 90% | Packet buffer memory: 4.1 MB | Switch type: Managed | Link aggregation: Yes | Jumbo frames support: Yes | Spanning tree protocol: Yes | Flow control support: Yes | Password protection: Yes | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 24 | ARP inspection: Yes | Jumbo frames: 9000 | Fanless: Yes | Cloud-managed: Yes