



TP-Link Omada 300Mbps Wireless N Ceiling Mount Access Point



Modelis: EAP110

Gamintojas: TP-LINK

EAN: 6935364091620

Prekės kodas: 538944

38.99€

Receiver sensitivity: 300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Do not expose to prolonged moisture. | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Avoid direct contact with water. | Product colour: White | Reset button: Yes | Antenna type: Internal | Frequency band: 2.4 - 2.4835 GHz | 5 GHz: No | 2.4 GHz: Yes | AC input voltage: 24 V | LED indicators: Power | Maximum data transfer rate: 300 Mbit/s | Sustainability compliance: Yes | Web-based management: Yes | MAC address filtering: Yes | Ethernet LAN data rates: 100 Mbit/s | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Ethernet LAN data rates: 10 | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.11b | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Transmitting power (CE): 19 dBm | Package depth: 268 mm | Package

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

width: 246 mm | Power over Ethernet (PoE): Yes | Width: 189.5 mm | 6 GHz: No | Harmonized System (HS) code: 85176990 | Security algorithms: WPA | Antennas quantity: 2 | Quick start guide: Yes | Syslog: Yes | Security algorithms: 64-bit WEP | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Security algorithms: WPA2-PSK | Height: 29.7 mm | Security algorithms: 128-bit WEP | Security algorithms: SNMP | Service Set Identifier (SSID) features: Multiple SSIDs | Operating relative humidity (H-H): 10 - 90% | Antenna gain level (max): 4 dBi | Quantity per pack: 1 pc(s) | Cabling technology: 10/100Base-T(X) | Access Control List (ACL): Yes | Operating temperature (T-T): 0 - 40 °C | Wireless isolation: Yes | Power consumption (typical): 2.8 W | Placement: Ceiling, Wall | Number of SSID supported: 8 | Package weight: 720 g | Rate limiting: Yes | PoE adapter included: Yes | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Mounting kit: Yes | Antenna direction type: Omni-directional | VLAN support: Yes | Ethernet LAN (RJ-45) ports: 1 | Wi-Fi Multimedia (WMM)/(WME): Yes | Cables included: AC | Power over Ethernet (PoE) type supported: Passive PoE | Package type: Box | Package height: 69 mm | Transmitting power (FCC): 21 dBm | Security algorithms: 152-bit WEP | Security algorithms: HTTPS | Security algorithms: SSH | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Depth: 170.5 mm | Virtual LAN features: VLAN mapping