



Infosec E4 Value 1000 uninterruptible power supply (UPS) Double- conversion (Online) 1 kVA 3 AC outlet(s)

Modelis: INF_674178

Gamintojas: INFOSEC

EAN: 3700085674178

Prekės kodas: 538970

435.99€

Certification: CE | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Store away from sources of heat and open flame. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Compliance certificates: RoHS | Input frequency: 47 - 63 Hz | Audible alarm modes: Alarm when on battery, Fault, Overload alarm, Low battery alarm | Power factor: 0.8 | Output voltage Total Harmonic Distortion (THD): 6% | Output operation voltage (min): 100 V | Depth: 220 mm | Output power capacity: 1 kVA | Efficiency: 88% | Serial ports quantity: 1 | Width: 145 mm | Maximum current: 10 A | Audible alarm(s): Yes | Typical backup time at half load: 9 min | AC outlet types: C13 coupler | Cold start: Yes | Display type: LED | Number of

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

output phases: 1 | Input operation voltage (max): 240 V | Output operation voltage (max): 240 V | Typical backup time at full load: 30 min | Input operation voltage (min): 100 V | Number of input phases: 1 | Battery recharge time: 4 h | Height: 282 mm | Battery technology: Sealed Lead Acid (VRLA) | Crest factor: 3:1 | AC outlets quantity: 3 AC outlet(s) | UPS topology: Double-conversion (Online) | ECO mode: Yes | Output frequency: 47/63 Hz | Form factor: Tower | Response time: 4 ms | Weight: 8.6 kg | Serial interface: Yes | Operating temperature (T-T): 0 - 40 °C | Input power factor: 0.99 | Waveform: Pure sine | Battery voltage: 12 V | Output voltage regulation: -1 - 1% | Cables included: Output power cable, RS-232, Input power cable | Battery capacity: 9 Ah | Product colour: Black | Operating relative humidity (H-H): 20 - 90% | Serial interface type: RS-232 | Charging current: 1 A | Noise level: 50 dB | Manual: Yes