



Canon PIXMA TS705a inkjet printer Colour 4800 x 1200 DPI A4 Wi-Fi

Modelis: 3109C026

Gamintojas: CANON

EAN: 4549292198423

Prekės kodas: 539049

91.98€

Hazard pictogram(s): Environmental hazard | Warnings: The product contains environmentally hazardous components. Dispose of in accordance with local regulations and do not dispose of in the rubbish. | Warnings: Avoid contact with ink. May cause skin and eye irritation. | Warnings: In the event of an ink spill, avoid inhaling vapours. | Hazard pictogram(s): Irritating or damaging | Total input capacity: 250 sheets | Duplex printing: Yes | Cartridge(s) included: Yes | Energy Star Typical Electricity Consumption (TEC): 0.2 kWh/week | Wi-Fi Direct: Yes | Paper tray media types: Plain paper | Other operating systems supported: iOS | Other operating systems supported: Android | Harmonized System (HS) code: 84433210 | Paper tray media types: Photo paper | Print speed (colour, draft quality, A4/US Letter): 10 ppm | Included cartridge capacity (CMY): 4 pages | Time to first page (black, normal): 8 s | Time to first page (colour, normal): 10 s | Total number of input trays: 1 | Borderless printing: Yes | Included cartridge capacity (black): 1 pages | Mac operating systems supported: Mac OS X 10.9 Mavericks | Mac operating systems supported: Mac OS X 10.3 Panther |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Built-in display: Yes | Windows operating systems supported: Windows 8.1 | USB 2.0 ports quantity: 1 | AC input voltage: 100 - 240 V | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): 5 - 35 °C | Weight: 5.4 kg | Windows operating systems supported: Windows 10 | Mac operating systems supported: Mac OS X 10.15 Catalina | Mac operating systems supported: Mac OS X 11.0 Big Sur | AC input frequency: 50 - 60 Hz | Windows operating systems supported: Windows 7 | Mac operating systems supported: Mac OS X 10.14 Mojave | Mac operating systems supported: Mac OS X 10.12 Sierra | Mac operating systems supported: Mac OS X 10.7 Lion | Display: LCD | Mac operating systems supported: Mac OS X 10.6 Snow Leopard | Mac operating systems supported: Mac OS X 10.4 Tiger | Mac operating systems supported: Mac OS X 10.2 Jaguar | Mac operating systems supported: Mac OS X 10.15.3 Catalina | Mac operating systems supported: Mac OS X 10.8 Mountain Lion | Product colour: Black | Mac operating systems supported: Mac OS X 10.11 El Capitan | Mac operating systems supported: Mac OS X 10.5 Leopard | Mac operating systems supported: Mac OS X 10.13 High Sierra | Power consumption (off): 0.3 W | Wi-Fi standards: 802.11g | Duplex printing mode: Auto | ISO B-series sizes (B0...B9): B5 | Photo paper sizes: 20x25 | Mobile printing technologies: Google Cloud Print | Mobile printing technologies: PIXMA Cloud Link | Height: 158 mm | Depth: 365 mm | Mobile printing technologies: Mopria Print Service | Maximum resolution: 4800 x 1200 DPI | Envelopes sizes: 10 | Photo paper sizes: 10x15 cm | Market positioning: Home & office | Wi-Fi: Yes | Non-ISO print media sizes: Letter | Number of print cartridges: 5 | Print speed (black, normal quality, A4/US Letter): 15 ppm | PictBridge: Yes | Width: 372 mm | Photo paper sizes: 13x18 | Cables included: AC | Ethernet LAN: Yes | USB port: Yes | Envelopes sizes: DL | ISO A-series sizes (A0...A9): A4 | Mobile printing technologies: Apple AirPrint | Photo paper sizes: 13x13 | ISO A-series sizes (A0...A9): A5 | Wi-Fi standards: 802.11b | Maximum ISO A-series paper size: A4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Printing colours: Black, Cyan, Magenta, Yellow | Colour: Yes | Server operating systems supported: Windows Server 2008 R2 | Server operating systems supported: Windows Server 2012 R2 | Server operating systems supported: Windows Server 2016