



TP-Link 28-Port Gigabit Easy Smart Switch with 24-Port PoE+



Modelis: TL-SG1428PE

Gamintojas: TP-LINK

EAN: 6935364072209

Prekės kodas: 539064

247.99€

Certification: CE, FCC, RoHS | AC input voltage: 100 - 240 V | AC input frequency: 50 - 60 Hz |
Product colour: Black | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1Q |
Networking standards: IEEE 802.3x | Web-based management: Yes | Networking standards: IEEE
802.3at | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking
standards: IEEE 802.1p | Networking standards: IEEE 802.3af | Auto-negotiation: Yes | Port mirroring:
Yes | Multicast support: Yes | Fiber ethernet cabling technology: 1000BASE-X | Virtual LAN features:
Port-based VLAN | Cable types supported: Cat4 | Rate limiting: Yes | Cable types supported: Cat3 |
Rack mounting: Yes | Virtual LAN features: Tagged VLAN | Flow control support: Yes | Harmonized
System (HS) code: 85176990 | Gigabit Ethernet (copper) ports quantity: 26 | Jumbo frames: 10000 |
Operating temperature (T-T): 0 - 50 °C | Cable types supported: Cat5 | Cable types supported: Cat5e
| Switch type: Managed | Link aggregation: Yes | Switch layer: L2 | Broadcast storm control: Yes |
Form factor: 1U | Cable types supported: Cat6 | Store-and-forward: Yes | Package height: 100 mm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Package width: 336 mm | Power over Ethernet plus (PoE+) ports quantity: 24 | Copper ethernet cabling technology: 10BASE-T | Warnings: Ensure the unit is adequately ventilated during operation. | Packet buffer memory: 4.1 MB | MAC address table: 8000 entries | Rack mount kit: Yes | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Copper ethernet cabling technology: 1000BASE-T | Forwarding rate: 41.7 Mpps | Power consumption (max): 1039.03 W | Power source: AC | Number of fans: 2 fan(s) | Power over Ethernet (PoE): Yes | Total Power over Ethernet (PoE) budget: 250 W | Auto MDI/MDI-X: Yes | Number of queues: 4 | Switching capacity: 56 Gbit/s | Width: 440 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Basic switching RJ-45 Ethernet ports quantity: 26 | Number of VLANs: 32 | Power supply included: Yes | IGMP snooping: Yes | VLAN support: Yes | Height: 44 mm | Package depth: 528 mm | Package weight: 3.94 kg | 10G support: No | Copper ethernet cabling technology: 100BASE-TX | User guide: Yes | Depth: 220 mm | Warnings: Do not open the case or try to repair it yourself. | Operating relative humidity (H-H): 10 - 90% | Cables included: AC | Security algorithms: SNMPv3 | Security algorithms: SNMPv2 | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Jumbo frames support: Yes | SFP module slots quantity: 2 | Storage relative humidity (H-H): 5 - 90% | Security algorithms: SNMP