



AG Neovo QM-4303 Flat panel monitor Digital Signage 43 500 cd/m 4K Ultra HD Black



Modelis: QM-4303

Gamintojas: AG NEOVO

EAN: 4710739598605

Prekės kodas: 539077

708.00€

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Display depth: 70 mm | USB port: Yes | Power consumption (standby): 0.5 W | Energy consumption (SDR) per 1000 hours: 99 kWh | Haze rate: 25% | Number of built-in speakers: 2 | VGA (D-Sub) input ports: 1 | USB version: 2.0 | Mounting type: Wall | Built-in speaker(s): Yes | Display height: 559 mm | Remote control included: Yes | Display width: 971 mm | Energy efficiency class (SDR): G | Display brightness: 500 cd/m² | Panel type: VA | Placement supported: Indoor | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | Energy efficiency scale: A to G | Orientation: Horizontal/Vertical | Operating hours (hours/days): 24/7 | Built-in processor: No | Display weight: 8 kg | Purpose: Universal | USB playback: Yes | Anti-glare screen: Yes | Remote (IR) output: 1 | Surface hardness: 3H | Computer system: No | USB ports quantity: 1 | PC Audio in: Yes | Warnings: Do not open the appliance housing, risk of electric shock. | Hazard

pictogram(s): GHS09: Environmental hazard | Warnings: The monitor contains substances hazardous

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be

išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

to health, including mercury avoid contact with damaged parts. | Hazard pictogram(s): GHS07: Harmful | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: REACH | Compliance certificates: WEEE | Compliance certificates: RoHS | Compliance certificates: CE | Cables included: AC | Package weight: 11.5 kg | Cables included: HDMI | Horizontal scan range: 15 - 135 kHz | Viewing angle, vertical: 178° | Operating temperature (T-T): 0 - 40 °C | Package depth: 144 mm | Ethernet LAN (RJ-45) ports: 1 | Product design: Digital signage flat panel | Product colour: Black | DVI port: No | HD type: 4K Ultra HD | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | HDMI ports quantity: 2 | Batteries included: Yes | Viewing angle, horizontal: 178° | Storage temperature (T-T): 20 - 80 °C | Power consumption (off): 0.3 W | AC input voltage: 100 - 240 V | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): -20 - 60% | HDMI version: 2.0 | Ethernet LAN: Yes | Power consumption (typical): 102 W | Display resolution: 3840 x 2160 pixels | Package height: 652 mm | Touchscreen: No | Package width: 1075 mm | Cable lock slot type: Kensington | Response time: 5 ms | RS-232 interface: Yes | Wi-Fi: No | VESA mounting: Yes | Display diagonal: 109.2 cm (43") | Native aspect ratio: 16:9 | Display number of colours: 1,07G | Pixel pitch: 0.245 x 0.245 mm | Panel mounting interface: 300 x 300 mm