



AG Neovo QM-5503 Flat panel monitor Digital Signage 55 500 cd/m 4K Ultra HD Black



Modelis: QM-5503

Gamintojas: AG NEOVO

EAN: 4710739598612

Prekės kodas: 539078

867.99€

Certification: CE LVD WEEE RoHS REACH EAC UKCA | USB playback: Yes | Energy efficiency class (SDR): G | Surface hardness: 3H | Energy consumption (SDR) per 1000 hours: 134 kWh | Panel type: VA | HDMI version: 2.0 | Built-in processor: No | USB port: Yes | Touchscreen: No | Purpose: Universal | RS-232 interface: Yes | DVI port: No | Panel mounting interface: 300 x 300 mm | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: WEEE | Ethernet LAN: Yes | Compliance certificates: REACH | Wi-Fi: No | VESA mounting: Yes | Power consumption (standby): 0.5 W | Placement supported: Indoor | USB version: 2.0 | Mounting type: Wall | Compliance certificates: Low Voltage Directive (LVD) | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Batteries included: Yes | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | Built-in speaker(s): Yes | Hazard pictogram(s): GHS09: Environmental hazard | HDMI ports quantity: 2 | Remote control included: Yes | Hazard pictogram(s): GHS07: Harmful |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Warnings: Do not open the appliance housing, risk of electric shock. | Display height: 709.2 mm | Display width: 1238.4 mm | Display brightness: 500 cd/m² | Display depth: 70 mm | Orientation: Horizontal/Vertical | Operating hours (hours/days): 24/7 | Haze rate: 25% | Number of built-in speakers: 2 | VGA (D-Sub) input ports: 1 | Computer system: No | Anti-glare screen: Yes | Energy efficiency scale: A to G | Remote (IR) output: 1 | Display weight: 13 kg | USB ports quantity: 1 | PC Audio in: Yes | Package width: 1390 mm | Cables included: HDMI | Power consumption (off): 0.3 W | Storage temperature (T-T): 20 - 80 °C | HD type: 4K Ultra HD | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | Viewing angle, horizontal: 178° | Display diagonal: 139.7 cm (55") | Package height: 830 mm | Package weight: 17.6 kg | Product colour: Black | Cable lock slot type: Kensington | Cables included: AC | Package depth: 144 mm | Response time: 5 ms | Operating temperature (T-T): 0 - 40 °C | Horizontal scan range: 15 - 135 kHz | Pixel pitch: 0.245 x 0.245 mm | Power consumption (typical): 102 W | Viewing angle, vertical: 178° | Product design: Digital signage flat panel | Operating relative humidity (H-H): -20 - 60% | Display number of colours: 1,07G | Ethernet LAN (RJ-45) ports: 1 | Display resolution: 3840 x 2160 pixels | AC input frequency: 50 - 60 Hz | AC input voltage: 100 - 240 V | Native aspect ratio: 16:9