



# Cudy PE25 network card Internal Ethernet 2500 Mbit/s



Modelis: PE25

Gamintojas: CUDY

EAN: 6971690791483

Prekės kodas: 539224

## 15.98€

Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows 11 | Height: 15 mm | Maximum data transfer rate: 2500 Mbit/s | Operating temperature (T-T): 0 - 70 °C | Package type: Box | Depth: 56 mm | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet LAN data rates: 1000 | Ethernet LAN data rates: 2500 Mbit/s | Ethernet LAN data rates: 100 Mbit/s | Interface: Ethernet | Weight: 37.2 g | Ethernet LAN: Yes | Ethernet LAN (RJ-45) ports: 1 | Connectivity technology: Wired | Width: 64 mm | Internal: Yes | Ethernet interface type: Gigabit Ethernet | Cabling technology: 2.5GBase-T | Component for: PC/Server | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 8 | Windows operating systems supported: Windows 10 | Ethernet LAN data rates: 10 | Storage temperature (T-T): -40 - 70 °C | Quick installation guide: Yes | LED indicators: Speed | Linux operating systems supported: Yes | LED indicators: Link | LAN controller: Realtek RTL8125-BG | Networking standards: IEEE 802.3u |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Networking standards: IEEE 802.3bz | Storage relative humidity (H-H): 5 - 90% | Wake-on-LAN ready: Yes | Server operating systems supported: Windows Server 2012 | LED indicators: Activity | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3az | Server operating systems supported: Windows Server 2022 | Resource CD: Yes | Mounting brackets included: Yes | Copper ethernet cabling technology: 1000BASE-TX | Flow control support: Yes | Host interface: PCI Express | PCI Card form factor: Full-height (low-profile) | Mean time between failures (MTBF): 376212 h | Auto MDIX IEEE: Yes | Copper ethernet cabling technology: 10BASE-T | Low-profile bracket: Yes