



Ever SINLINE RT 2000 Line- Interactive 2 kVA 1650 W 8 AC outlet(s)

Modelis: W/SRTLRT-002K00/00

Gamintojas: EVER

EAN: 5907683603731

Prekės kodas: 539269

922.00€

Input operation voltage (min): 178 V | LED indicators: Yes | Number of input phases: 1 | Waveform: Sine | Number of output phases: 1 | Storage temperature (T-T): 0 - 45 °C | Input operation voltage (max): 281 V | Output power: 1650 W | Operating temperature (T-T): 0 - 40 °C | Package height: 247 mm | Battery voltage: 12 V | Output power capacity: 2 kVA | AC outlet types: C13 coupler | Rubber feet: Yes | Cooling type: Active | USB 2.0 ports quantity: 1 | Operating altitude: 0 - 1000 m | Power plug: C20 coupler | UPS topology: Line-Interactive | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | AC outlets quantity: 8 AC outlet(s) | Battery capacity: 7 Ah | Number of batteries supported: 4 | Ethernet LAN (RJ-45) ports: 1 | Automatic Voltage Regulation (AVR): Yes | Depth: 460 mm | Form factor: Rackmount/Tower | Package width: 547 mm | Width: 440 mm | International Protection (IP) code: IP20 | Input frequency: 50 Hz | Weight: 26 kg | Emergency Power Off (EPO): Yes | Cold start: Yes | Storage relative humidity

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(H-H): 20 - 95% | Typical backup time at full load: 3 min | Product colour: Black | Quick installation guide: Yes | Power protection features: Overload | Power protection features: Short circuit | Number of phases: 1 | Cables included: Input power cable | Output operation voltage (max): 253 V | Height: 132 mm | Battery recharge time: 4 h | Typical backup time at half load: 6 min | Output operation voltage (min): 195 V | Maximum current: 16 A | Operating relative humidity (H-H): 20 - 80% | Display type: LCD | Surge protection: Yes | Manual: Yes